## ASUS ROG MAXIMUS Z790 HERO EVA-02 EDITION Intel Z790 LGA 1700 ATX

Marca: ASUS Código del producto: 90MB1FL0-M0AAY0

Nombre del producto: ROG MAXIMUS Z790 HERO

**EVA-02 EDITION** 

ASUS ROG MAXIMUS Z790 HERO EVA-02 EDITION. Fabricante de procesador: Intel, Socket de procesador: LGA 1700, Procesador compatible: Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ .... tipos de memoria compatibles: DDR5-SDRAM, Memoria interna máxima: 192 GB, Tipo de ranuras de memoria: DIMM. Interfaces de disco de almacenamiento soportados: M.2, SATA III, Tipos de unidades de almacenamiento admitidas: HDD & SSD, Niveles RAID: 0, 1, 5, 10. Tipo de interfaz ethernet: 2.5 Gigabit Ethernet, Máximo estándar Wi-Fi: Wi-Fi 6E (802.11ax), Estándares de Wi-Fi: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E.... Componente para: PC, Factor de forma de la tarjeta madre: ATX, Familia del chipset: Intel





Processor			Rear panel I/O ports	
Processor manufacturer * Processor socket *		Intel LGA 1700	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
		Intel® Celeron®, Intel® Pentium® Gold, Intel® Core™ i3, Intel®	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	5
Compatible processor series *		Core™ i5, Intel® Core™ i7, Intel® Core™ i9	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Supported processor sockets		LGA 1700	Ethernet LAN (RJ-45) ports *	1
Memory			HDMI ports quantity *	1
Supported memory types * Number of memory slots * Memory slots type Memory channels	DDR5-SDRAM 4		Headphone outputs	1
	DIMM Dual-channel		Microphone in	✓
ECC compatibility	Non-ECC	00,6800,6600,6400,6200,6000,5800,5600,5400,5200,5000,4800	S/PDIF out port	✓
Supported memory clock speeds Supported memory clock speed	MHz	00,0000,0000,0400,0200,0000,3000,3000,3400,3200,3000,4000	Thunderbolt ports quantity	2
(max)  Maximum internal memory *	7800 MHz 192 GB		WiFi-AP antenna jack	1
Unbuffered memory	1		Network	
Storage controllers			Ethernet LAN	1
Supported storage drive types		HDD & SSD M.2, SATA III	Ethernet interface type	2.5 Gigabit Ethernet
Supported storage drive interfaces *			Wi-Fi *	✓ Siguilit Ethernet
Number of HDDs supported		6	Top Wi-Fi standard	Wi-Fi 6E (802.11ax)
Number of storage drives supported		11	Top Wi-11 Standard	802.11a, 802.11b, 802.11g, Wi-Fi 4
RAID support		✓	Wi-Fi standards	(802.11a), Wi-Fi 5 (802.11ac), Wi-Fi
RAID levels		0, 1, 5, 10		6 (802.11ax), Wi-Fi 6E (802.11ax)
Graphics			Bluetooth	✓
Parallel processing technology			Bluetooth version	5.3
support *		Not supported	Features	
Internal I/O			Motherboard chipset *	Intel Z790
USB 2.0 connectors *		2	Audio chip	Realtek ALC4082
USB 3.2 Gen 1 (3.1 Gen 1)		2	Audio output channels *	7.1 channels
connectors *			Component for *	PC
Number of SATA III connectors * 6		6	Motherboard form factor *	ATX

Internal I/O		Features	
Front panel audio connector ATX Power connector (24-pin) CPU fan connector	<ul><li>✓</li><li>✓</li><li>✓</li><li>✓</li></ul>	Motherboard chipset family * Windows operating systems supported	Intel Windows 10 x64, Windows 11
Number of chassis fan connectors		Expansion slots	
EPS power connector (8-pin) 12V power connector		PCI Express x16 (Gen 4.x) slots PCI Express x16 (Gen 5.x) slots Number of M.2 (M) slots	1 2 5
RGB LED pin header	<b>V</b>	BIOS	
		BIOS type * BIOS memory size Clear CMOS button	UEFI AMI 256 Mbit ✓
		Weight & dimensions	
		Width Depth	305 mm 244 mm
		Packaging content	
		Cables included	SATA

