

EZVIZ H8 Pro 2K Esférico Cámara de seguridad IP Interior y exterior 2304 x 1296 Pixeles Techo/pared

Marca: EZVIZ Código del producto: CS-H8-R100-1J3WKFL

Nombre del producto: H8 Pro 2K

EZVIZ H8 Pro 2K. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Esférico. Ángulo de visión del objetivo, horizontal: 89°, Ángulo de visión del objetivo, vertical: 46°, Ángulo de visión de la lente, diagonal: 104°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Distancia focal fija: 4 mm





Dorformanso		Video	
Performance			
Type *	IP security camera	Digital Wide Dynamic Range (DWDR)	✓
Placement supported * Connectivity technology *	Indoor & outdoor Wired & Wireless		
, ,,	Wiled & Wileless	Audio	
Auto-tracking	•	Built-in speaker(s)	✓
Preset points	✓	Audio system	2-way
Wide Dynamic Range (WDR)	✓	Network	
Day/night mode	•	Ethernet LAN *	✓
Infrared (IR) cut-off filter	•	Ethernet interface type	Fast Ethernet
Remote viewing	✓	Wi-Fi *	✓
Certification	UL / FCC / CE / WEEE / RoHS / UKCA	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Design		Bluetooth *	×
Form factor *	Spherical	Storage	
Mounting type *	Ceiling/wall	Built-in HDD *	×
Product colour *	White	Card reader integrated	✓
LED indicators	V	Compatible memory cards	MicroSD (TransFlash)
Protection features	Waterproof	Maximum memory card size	512 GB
Weatherproof	✓	Ports & interfaces	
Camera		Ethernet LAN (RJ-45) ports	1
Camera pan control	✓		-
Camera tilt control	✓	Security	
Minimum illumination	0 lx	Built-in siren	✓
Lens viewing angle, horizontal	89°	Password protection	✓
Lens viewing angle, vertical	46°	Security algorithms	WPA-PSK, WPA2-PSK
Lens viewing angle, diagonal	104°	Alert notification type	Push notification
Tilt angle range	0 - 80°		

Camera		Security	
Pan range	0 - 340°	Intelligent Video Surveillance (IVS) system features	Human detection, Vehicle detection
Image sensor		Anti-flicker	✓
Number of sensors	1	Heartbeat	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Digital watermark	✓
Progressive scan	√	Power	
Sensor type *	CMOS		DC
Lens system		Power source type * Power consumption (max)	6 W
Zoom capability	✓	DC output voltage	12
Number of lenses *	1	DC output current	1 A
Maximum aperture number Fixed focal length	1.6 4 mm	Operational conditions	
Night vision		Operating temperature (T-T)	-30 - 50 °C
		Operating relative humidity (H-H)	0 - 95%
Night vision *	√ 30 m	Weight & dimensions	
Night vision distance B/W night vision distance	30 m	Width	116 mm
Colour night vision distance	20 m	Depth	153.2 mm
LED type	IR	Height	163.8 mm
Video		Weight	592 g
Maximum resolution *	2304 x 1296 pixels	Packaging data	
Total megapixels *	5 MP	Package width	187 mm
Video compression formats	H.264, H.265	Package depth	174 mm
Frame rate	30 fps	Package height	186.5 mm
Video streaming	✓	Package weight	943 g
Noise reduction	✓	Sustainability	
Noise reduction technology	3D noise reduction	Sustainability compliance	✓
Bit rate	2 Mbps	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS, UKCA, WEEE
		Packaging content	
		Number of cameras *	1
		Screws included	✓
		Drilling template included	✓
		Mounting template	✓

