QNAP

QNAP TVS-h474 NAS Tower Intel® Pentium® G7400 8 GB DDR4 0 TB QuTS hero Negro

Marca: QNAP Código del producto: TVS-H474-PT-8G-US

Nombre del producto: TVS-h474

QNAP TVS-h474. Tipo: NAS. Tipo de chasis: Tower. Clase del dispositivo: Pequeñas y medianas empresas. Familia de procesador: Intel® Pentium®, Modelo del procesador: G7400, Frecuencia del procesador: 3.7 GHz. Memoria interna: 8 GB, Tipo de memoria interna: DDR4. Capacidad de almacenamiento total instalado: 0 TB. Sistema operativo instalado: QuTS hero





Storage		Design	
Supported storage drive interfaces	M.2, Serial ATA II, Serial ATA III	Cable lock slot type	Kensington
Storage drive sizes supported	2.5,3.5,M.2	Performance	
Number of M.2 (M & B) slots RAID support * RAID levels Online RAID expansion RAID rebuild Hot-swap drive bays Supported file systems Storage drives installed * Total installed storage capacity * Number of storage drives supported	2 v 0, 1, 5, 6, 10, JBOD v FAT32, HFS+, NTFS, ZFS, exFAT, ext3, ext4 X 0 TB	Type * Device class * Backup function * Backup features Buzzer Multilingual support Snapshot Management protocols Share folder access right management	NAS Small & Medium Business Cloud, iSCSI LUN SNMP V2/V3
* Installed storage drive type * Supported storage drive types * Disk roaming	4 X HDD & SSD ✓	Security algorithms Access Control List (ACL) Reset button	256-bit AES, FIPS 140-2, HTTPS, SSH, SSL/TLS, TLS
Processor	•	On/off switch	✓
Processor manufacturer * Processor family * Processor model * Processor frequency * Processor cores Processor threads Bus type CPU configuration (max) On-board graphics card model	Intel Intel® Pentium® G7400 3.7 GHz 2 4 DMI4 1 Intel UHD Graphics 710	Built-in FTP server Browser supported System log Hot spare Disk scan S.M.A.R.T. support Share folder USB copy function	Apple Safari, Mozilla Firefox, Google Chrome, Microsoft Edge
Memory		Software	
Internal memory * Internal memory type Maximum RAM supported Memory slots Memory form factor Flash memory	8 GB DDR4 64 GB 2 SO-DIMM 5000 MB	Operating system installed * Operating system version Windows operating systems supported Linux operating systems supported	QuTS hero h5.0.0 Windows 10, Windows 11, Windows 7, Windows 8 CentOS 7.0, Ubuntu 14.04, openSUSE 12.1, openSUSE 12.2

Network		Software	
Ethernet LAN * Ethernet LAN data rates Ethernet LAN data rate supported (max) DHCP server Jumbo frames support	10,100,1000,2500 Mbit/s 10000 Mbit/s	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey
SCSI support Wake-on-LAN ready Supported network protocols IPv4, IPv6	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019	
Dynamic DNS (DDNS)	√	Other operating systems supported	IBM AIX 7.1, Solaris 10
	-	Power	
Ports & interfaces		Power supply location	Built-in
ISB port * ISB 3.2 Gen 2 (3.1 Gen 2) Type-A orts quantity ISB 3.2 Gen 2 (3.1 Gen 2) Type-C orts quantity IDMI ports quantity 1	Power supply unit (PSU) capacity Number of power supply units Power consumption (typical) Power consumption (sleep) AC input voltage Fan voltage	250 W 1 78.574 W 34.906 W 100 - 240 V 12 V	
HDMI version Ethernet LAN (BL 45) ports *	1.4b	Weight & dimensions	
Concurrent connections PCI Express x2 (Gen 3.x) slots	2 700 2 1	Width * Depth * Height *	199.3 mm 280.2 mm 188.2 mm
Design		Packaging content	
Chassis type * Cooling type * Product colour Number of fans Fan diameter Fan diameter 2 Drive bay locking LED indicators Built-in display Display type Cable lock slot	Tower Active Black 2 fan(s) 12 cm 6 cm ✓ HDD, LAN, M.2, Status, USB ✓ LCD ✓	Cables included Power cables quantity Number of screws Drive tray key included Processor special features Embedded options available Enhanced Intel SpeedStep Technology Execute Disable Bit Idle States Intel 64 Intel Virtualization Technology (VT-x) Intel Virtualization Technology for Directed I/O (VT-d) Intel VT-x with Extended Page Tables (EPT)	AC, LAN (RJ-45) 1 28
		Operational conditions	
		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C





885022024704

0885022024704

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.