

## Allied Telesis GS950/10PS-V2 Gestionado Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Plata

**Marca :** Allied Telesis

**Código del producto:** AT-GS950/10PS-V2-10

**Nombre del producto :** GS950/10PS-V2



Allied Telesis GS950/10PS-V2. Tipo de interruptor: Gestionado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 20 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Conector eléctrico: Toma de entrada de CC. Energía sobre Ethernet (PoE). Montaje de pared, Montaje en rack

Management features		Security	
Switch type *	Managed	MAC address filtering	✓
Web-based management	✓	Multicast features	
System event log	✓	Multicast support	✓
Ports & interfaces		Design	
Basic switching RJ-45 Ethernet ports quantity *	8	Rack mounting *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Product colour	Silver
SFP module slots quantity	2	Wall mountable	✓
Power connector	DC-in jack	Performance	
Network		Internal memory	256 MB
	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Flash memory	32 MB
Networking standards *		Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Port mirroring	✓	Power over Ethernet plus (PoE+) ports quantity	8
Flow control support	✓	Total Power over Ethernet (PoE) budget	75 W
Link aggregation	✓	Operational conditions	
Broadcast storm control	✓	Operating temperature (T-T)	0 - 40 °C
Rate limiting	✓	Storage temperature (T-T)	-25 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	5 - 90%
Number of VLANs	256	Storage relative humidity (H-H)	5 - 95%
Data transmission		Weight & dimensions	
Switching capacity *	20 Gbit/s	Width	330 mm
Throughput	14.88 Mpps	Depth	180 mm
MAC address table *	16000 entries	Height	44 mm
Packet buffer memory	1.5 MB	Weight	1.9 kg
Security			
DHCP features	DHCP client		
IGMP snooping	✓		



0767035219127



767035219127

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date