
Samsung LH50QMCEBGCXGO pantalla de señalización Pantalla plana de señalización digital 127 cm (50") LCD Wifi 500 cd / m² 4K Ultra HD Procesador incorporado Tizen 24/7

Marca : Samsung Código del producto: LH50QMCEBGCXGO

Nombre del producto : LH50QMCEBGCXGO







Display		Design	
Panel type Display diagonal * Display technology * Display resolution * Display brightness * HD type * Touchscreen * Native aspect ratio Response time Contrast ratio (typical) Dynamic contrast ratio marketing name Viewing angle, horizontal Viewing angle, vertical Display number of colours Pixel pitch Number of displays Colour saturation Horizontal scan range Vertical scan range Haze rate	VA 127 cm (50") LCD 3840 x 2160 pixels 500 cd/m² 4K Ultra HD X 16:9 8 ms 4000:1 Mega Contrast 178° 1 billion colours 0.285 x 0.285 mm 1 72% 30 - 81 kHz 48 - 75 Hz 25%	Bezel width (bottom) Bezel width (side) Bezel width (top) Anti-glare screen Mounting type Performance Purpose * Multi-display supported Multicast support Operating hours (hours/days) HDCP International Protection (IP) code HDCP version Power Power consumption (typical) * Power consumption (standby) * Power consumption (sleep) AC input voltage AC input frequency	1.15 cm 1.15 cm 1.15 cm 1.15 cm Wall Commercial IP5X 2.2 132 W 0.5 W 0.5 W 100 - 240 V 50/60 Hz
Ports & interfaces		Computer system	
HDMI ports quantity * HDMI version HDMI input ports quantity DVI port * DisplayPorts quantity * DisplayPorts in	3 2.0 3 x 1	Computer system * Computer system type Built-in processor * Processor frequency Internal storage capacity Operating system installed Operating system version	System on Chip (SoC) 1.6 GHz 16 GB Tizen 7.0

Ports & interfaces		Weight & dimensions	
USB port * USB ports quantity 2 USB version 2.0 Ethernet LAN * ✓	Display width Display depth Display height Display weight	1124.1 mm 28.5 mm 644.8 mm 11.8 kg	
Ethernet LAN (RJ-45) ports	1	Packaging content	
Wi-Fi *	•	Remote control included	✓
RS-232 interface	•	Batteries included	✓
Infrared data port	✓	Cables included	RS-232
Audio		Operational conditions	
Built-in speaker(s) * Number of built-in speakers	2	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%
RMS rated power	10 W	Certificates	
Design Product design *	Digital signage flat panel Indoor	Certification	EMC - Class B, Safety - 60950-1, 62368-1
Placement supported *		Features	
Orientation	Horizontal/Vertical	Wall mountable	✓
VESA mounting * Panel mounting interface	200 x 200 mm	Technical details	
		Sustainability certificates	ENERGY STAR, EPEAT Bronze

