Samsung LH75QMCEBGCXGO pantalla de señalización Pantalla plana de señalización digital 190.5 cm (75") LCD Wifi 500 cd / m² 4K Ultra HD Negro Procesador incorporado Tizen 24/7

Marca : Samsung Código del producto: LH75QMCEBGCXGO

Nombre del producto: LH75QMCEBGCXGO

Samsung LH75QMCEBGCXGO. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 190.5 cm (75"), Tecnología de visualización: LCD, Resolución de la pantalla: 3840 x 2160 Pixeles, Brillo de pantalla: 500 cd / m², Tipo HD: 4K Ultra HD. Wifi. Horas de funcionamiento (horas/días): 24/7. Sistema operativo instalado: Tizen. Color del producto: Negro





Display		Design	
Panel type VA Display diagonal * 190.5 cm (75") Display technology * LCD	190.5 cm (75")	Bezel width (top) Anti-glare screen Mounting type	1.34 cm ✓ Wall
Display resolution * Display brightness * HD type * Touchscreen * Response time Contrast ratio (typical) Dynamic contrast ratio marketing name Viewing angle, horizontal Viewing angle, vertical Pixel pitch Horizontal scan range	3840 x 2160 pixels 500 cd/m² 4K Ultra HD x 8 ms 4000:1 Mega Contrast 178° 178° 0.429 x 0.429 mm 30 - 81 kHz	Performance Purpose * Operating hours (hours/days) HDCP HDCP version Power Power consumption (typical) * Power consumption (standby) * AC input voltage AC input frequency	Universal 24/7 ✓ 2.2 214.5 W 0.5 W 100 - 240 V 50/60 Hz
Vertical scan range	48 - 75 Hz	Computer system	
Haze rate Ports & interfaces HDMI ports quantity * HDMI version	25% 3 2.0	Built-in processor * Internal memory Operating system installed Operating system version	✓ 16 GB Tizen 7.0
DVI port *	X	Weight & dimensions	
DisplayPorts quantity * 1 DisplayPorts in 1 USB port * USB ports quantity 2	Display width Display depth Display height Display weight	1682.3 mm 28.5 mm 960.4 mm 33.4 kg	
Ethernet LAN *	✓	Packaging data	
Ethernet LAN (RJ-45) ports 1 Wi-Fi * RS-232 interface Infrared data port	· · · · · · · · · · · · · · · · · · ·	Package width Package depth Package height Package weight	1839 mm 180 mm 1113 mm 44.1 kg
Card reader integrated	×	Operational conditions	
		Operating temperature (T-T)	0 - 40 °C

Audio		Operational conditions		
Built-in speaker(s) *	1	Operating relative humidity (H-H)	10 - 80%	
RMS rated power	10 W	Certificates		
Design		Certification	60950-1, 62368-1	
Product design *	Digital signage flat panel	Features		
Placement supported *	Indoor/outdoor	Suitable for indoor use	/	
Product colour * VESA mounting *	Black ✓	Wall mountable	✓	
Panel mounting interface	400 x 400 mm	Technical details		
Bezel width (bottom)		Sustainability compliance	✓	
Bezel width (side)		Sustainability certificates	ENERGY STAR, EPEAT Bronze	
		Compliance certificates	CE, cTUVus	
		Other features		
		Bluetooth	✓	

