

Samsung QB85R-B Pantalla plana de señalización digital 2.16 m (85") TFT Wifi 350 cd / m² 4K Ultra HD Negro Procesador incorporado Tizen 4.0



Marca : Samsung

Código del producto: LH85QBRBBGCXZA

Nombre del producto : QB85R-B

Samsung QB85R-B. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 2.16 m (85"), Tecnología de visualización: TFT, Resolución de la pantalla: 3840 x 2160 Pixeles, Brillo de pantalla: 350 cd / m², Tipo HD: 4K Ultra HD. Wifi. Sistema operativo instalado: Tizen 4.0. Color del producto: Negro



Display		Design	
Panel type	VA	Mounting type	Wall
Display diagonal *	2.16 m (85")	Purpose *	Universal
Display technology *	TFT	HDCP	✓
Display resolution *	3840 x 2160 pixels	HDCP version	2.2
Display brightness *	350 cd/m ²	Power	
HD type *	4K Ultra HD	Power consumption (typical) *	198 W
Touchscreen *	✗	Power consumption (standby) *	0.5 W
Native aspect ratio	16:9	AC input voltage	100 - 240 V
Response time	6 ms	AC input frequency	50/60 Hz
Contrast ratio (typical)	4000:1	Computer system	
Dynamic contrast ratio marketing name	Mega Contrast	Computer system *	✓
Viewing angle, horizontal	178°	Built-in processor *	✓
Viewing angle, vertical	178°	Internal storage capacity	8 GB
Pixel pitch	0.4875 x 0.4875 mm	Operating system installed	Tizen 4.0
Colour saturation	92%	Video formats supported	AVC, AVS+, H.263, H.264, HEVC, MPEG, MPEG1, MPEG2, MPEG4, VC-1, VP8, VP9
Horizontal scan range	30 - 81 kHz	Audio formats supported	AC3
Vertical scan range	48 - 75 Hz	Image formats supported	JPEG, PNG
Haze rate	2%	Weight & dimensions	
Ports & interfaces		Width (with stand)	1897.8 mm
HDMI ports quantity *	2	Depth (with stand)	56.7 mm
DVI port *	✓	Height (with stand)	1080.8 mm
DVI-D ports quantity	1	Weight (with stand)	48.4 kg
USB port *	✓	Packaging data	
USB ports quantity	2	Package width	2090 mm
USB version	2.0	Package depth	260 mm
Ethernet LAN *	✓	Package height	1247 mm
Wi-Fi *	✓	Package weight	63.7 kg
RS-232 interface	✓		
Design			
Product design *	Digital signage flat panel		

Design		Packaging content	
Placement supported *	Indoor	Remote control included	✓
Orientation	Horizontal/Vertical	Batteries included	✓
Product colour *	Black	Power adapter included	✓
VESA mounting *	✓		
Panel mounting interface	600 x 400 mm		
Operational conditions			
		Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	10 - 80%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.