



Dahua Technology WizSense DH-IPC-HDBW3441R-ZAS-S2 cámara de vigilancia Domo Cámara de seguridad IP Exterior 2688 x 1520 Pixeles Techo

Marca : Dahua Technology

Familia de productos: WizSense

Código del producto: DH-IPC-HDBW3441R-ZAS-S2

Nombre del producto : DH-IPC-HDBW3441R-ZAS-S2

Dahua Technology WizSense DH-IPC-HDBW3441R-ZAS-S2. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Domo. Ángulo de rotación: 355°, Ángulo de visión del objetivo, horizontal: 104 - 29°, Ángulo de visión del objetivo, vertical: 54 - 16°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"). Intervalo de longitud focal: 2.7 - 13.5 mm, Distancia de detección (angular): 64 m, Distancia de detección (tele): 210 m

Performance		Video	
Type *	IP security camera	Gain control type	Auto
Placement supported *	Outdoor	Privacy masking	✓
Connectivity technology *	Wired	Image stabilizer	✓
Wide Dynamic Range (WDR)	✓	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Day/night mode	✓	Bit rate	3 kbps - 8192 kbps
Alarm input/output	✓	Back Light Compensation (BLC)	✓
Dynamic range	120 dB	Highlight Compensation (HLC)	✓
Design		Region of Interest (ROI) encoding	✓
Form factor *	Dome	Audio	
Mounting type *	Ceiling	Audio input channels	1 channels
Product colour *	White	Audio output channels	1 channels
Housing material	Metal	Signal-to-Noise Ratio (SNR)	56 dB
International Protection (IP) code	IP67	Built-in microphone	✓
IK code	IK10	Voice codecs	G.711Mu, G.711a, G.723, G.726, PCM
Camera		Network	
Camera pan control	✓	Ethernet LAN *	✓
Camera tilt control	✓	Ethernet interface type	Fast Ethernet
Minimum illumination	0 lx	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP; P2P
Angle of rotation	355°		
Lens viewing angle, horizontal	104 - 29°		
Lens viewing angle, vertical	54 - 16°	Wi-Fi *	✗
Lens viewing angle, diagonal	125 - 33°	Bluetooth *	✗
Tilt angle range	0 - 80°	Number of users	20 user(s)
Pan range	0 - 355°	Storage	
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Built-in HDD *	✗
Camera shutter type	Electronic	Card reader integrated	✓
Camera shutter speed	1/3 - 1/100000 s	Compatible memory cards	MicroSD (TransFlash)
Adjustment shutter speed	Auto/Manual	Maximum memory card size	256 GB
Number of Privacy masking areas	4	Internal memory	512 MB
Image sensor		ROM capacity	128 MB
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Ports & interfaces	
Progressive scan	✓	Ethernet LAN (RJ-45) ports	1
Sensor type *	CMOS	Security	
Lens system		Alarm input channels	1
Focal length range	2.7 - 13.5 mm		
Minimum aperture number	1.5		
Detect distance (wide)	64 m		

Lens system		Security	
Detect distance (tele)	210 m	Alarm output channels	1
Observe distance (wide)	25.6 m	Video motion detection	✓
Observe distance (tele)	84 m	Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Recognize distance (wide)	12.8 m	Mirror	✓
Recognize distance (tele)	42 m	Management features	
Identify distance (wide)	6.4 m	Web browser	✓
Identify distance (tele)	21 m	Power	
Closest focusing distance	0.8 m	Power source type *	DC, PoE
Night vision		Power consumption (typical)	2.8 W
Night vision *	✓	Power consumption (max)	7.9 W
Night vision distance	40 m	Power consumption (Power over Ethernet (PoE))	3.6 W
LED type	IR	DC output voltage	12
Number of illumination LEDs	3	Operational conditions	
Video		Operating temperature (T-T)	-30 - 60 °C
Maximum resolution *	2688 x 1520 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	4 MP	Operating relative humidity (H-H)	0 - 95%
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG	System requirements	
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2560 x 1440, 2688 x 1520	Mobile operating systems supported	Android, iOS
Video recording	✓	Weight & dimensions	
Frame rate	30 fps	Height	94 mm
Video streaming	✓	Diameter	12.2 cm
Noise reduction	✓	Weight	713 g
Noise reduction technology	3D noise reduction	Packaging data	
		Package weight	986 g
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date