

## Dahua Technology Lite HAC-HDW1200T-IL-A cámara de vigilancia Domo Cámara de seguridad IP Interior y exterior 1920 x 1080 Pixeles Techo/pared

Marca : Dahua Technology Familia de productos: Lite Código del producto: HAC-HDW1200T-IL-A

Nombre del producto: HAC-

HDW1200T-IL-A

Dahua Technology Lite HAC-HDW1200T-IL-A. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Domo. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 102°, Ángulo de visión del objetivo, vertical: 60°. Tipo de sensor: CMOS, Número de píxeles efectivos (A x V): 1920 x 1080 Pixeles. Distancia de detección: 41.1 m, Distancia de observación: 16.5 m, Distancia de reconocimiento: 8.3 m

Performance		Video	
· ·	IP security camera Indoor & outdoor	Maximum resolution * Total megapixels *	1920 x 1080 pixels 2 MP
Connectivity technology * Wide Dynamic Range (WDR)	Wired ✓	Supported graphics resolutions	960 x 480, 960 x 576, 1920 x 1080 (HD 1080)
Day/night mode	•	Supported video modes	1080p
Built-in light	·	Frame rate	30 fps
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B; UL: UL62368-1 + CAN/CSA C22.2 No. 62368-1-14	Noise reduction	<b>✓</b>
		Noise reduction technology	3D noise reduction
		Gain control type	Auto 🗸
Design	•	Privacy masking Bit rate control	Constant Bit Rate (CBR)
Form factor *	Dome	Back Light Compensation (BLC)	✓
Mounting type *	Ceiling/wall	Highlight Compensation (HLC)	· ·
Product colour *	White	Digital Wide Dynamic Range	
Housing material	Metal	(DWDR)	✓
Protection features	Dust resistant, Waterproof	Smart IR	✓
International Protection (IP) code	IP67	Audio	
Camera		Audio input channels	1 channels
Minimum illumination	0 lx	Signal-to-Noise Ratio (SNR)	65 dB
Angle of rotation	360°	Built-in microphone	✓
Lens viewing angle, horizontal	102° 60°	Network	
Lens viewing angle, vertical  Lens viewing angle, diagonal	129°	Ethernet LAN *	×
Tilt angle range	0 - 78°	Wi-Fi *	×
Pan range	0 - 360°	Bluetooth *	×
White balance	Area white balance, Auto	Storage	
Camera shutter type	Electronic	Built-in HDD *	×
Camera shutter speed	1/30 - 1/100000 s		*
Number of Privacy masking areas	8	Ports & interfaces	
Image sensor		BNC output ports	1
Number of sensors	2	Security	
Progressive scan	<b>√</b>	Mirror	✓
Sensor type * Number of effective pixels (H x V)	CMOS 1920 x 1080 pixels	Power	
·	1320 V 1000 hiveiz	Power source type *	DC
Lens system	41.1	Power consumption (max)	4.1 W
Detect distance Observe distance	41.1 m 16.5 m	DC output voltage	12
Recognize distance	8.3 m	Operational conditions	
Fixed focus	<b>√</b>	Operating temperature (T-T)	-40 - 60 °C

Lens system		Operational conditions	
Maximum aperture number Identify distance Fixed focal length	2 4.1 m 2.8 mm	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 60 °C 0 - 95% 0 - 95%
Closest focusing distance	0.5 m	Weight & dimensions	
Night vision		Height	99.2 mm
Night vision * Night vision distance	<b>√</b> 40 m	Diameter Weight	10.6 cm 450 g
LED type	IR/White	Packaging data	
Number of illumination LEDs	4	Package weight	580 g
		Packaging content	
		Number of cameras *	1

