

Dahua Technology Pro DH-HAC-HFW2802TUN-Z-A cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Exterior 3840 x 2160 Pixeles Pared

Marca : Dahua Technology Familia de productos: Pro Código del producto: DH-HAC-HFW2802TUN-Z-A

Nombre del producto : DH-HAC-HFW2802TUN-Z-A

Dahua Technology Pro DH-HAC-HFW2802TUN-Z-A. Tipo: Cámara de seguridad CCTV, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 113 - 47°, Ángulo de visión del objetivo, vertical: 60 - 26°. Tipo de sensor: CMOS. Zoom digital: 4x, Intervalo de longitud focal: 2.7 - 13.5 mm, Distancia de detección (angular): 83.4 m

Performance		Night vision	
Type * CCTV security camera Placement supported * Outdoor Connectivity technology * Wired Wide Dynamic Range (WDR) ✓	Outdoor Wired	Night vision * Night vision distance LED type Number of illumination LEDs	√ 80 m IR 4
Day/night mode	√	Video	
Dynamic range	120 dB	Maximum resolution *	3840 x 2160 pixels
Posign Form factor * Mounting type * Product colour * Housing material International Protection (IP) code	Bullet Wall White Metal IP67	Supported graphics resolutions Analog signal format system Noise reduction Noise reduction technology Gain control type	960 x 480, 960 x 576, 2560 x 1440, 2880 x 1620, 3860 x 2160 NTSC ✓ 3D noise reduction Auto/Manual
Camera		Privacy masking	V
Camera pan control Camera tilt control Minimum illumination 0 lx		Back Light Compensation (BLC) Highlight Compensation (HLC) Smart IR	<i>y y</i>
Angle of rotation	360°	Audio	
Lens viewing angle, horizontal 113 - 47° Lens viewing angle, vertical 60 - 26° Lens viewing angle, diagonal 133 - 53°	60 - 26°	Audio input channels Signal-to-Noise Ratio (SNR) Built-in microphone	1 channels 65 dB
Tilt angle range	0 - 90°	Network	
Pan range White balance Camera shutter type Camera shutter speed Number of Privacy masking areas	hite balance Area white balance, Auto amera shutter type Electronic amera shutter speed 1/4 - 1/100000 s	Ethernet LAN * Wi-Fi * Bluetooth *	x x x
Image sensor		Storage	
Progressive scan Sensor type *	✓ CMOS	Ports & interfaces	1
Lens system		BNC output ports	1
Zoom capability Digital zoom	✓ 4x	Security Mirror	✓
Focal length range	2.7 - 13.5 mm	Power	
Auto focus Minimum aperture number Detect distance (wide) 1.5 83.4 m	1.5 83.4 m	Power source type * Power consumption (max) DC output voltage	DC 13.9 W 12, 24
Detect distance (tele) Observe distance (wide) Observe distance (tele)	189.6 m 33.4 m 75.8 m	Operational conditions Operating temperature (T-T)	-30 - 60 °C

Lens system		Operational conditions	
Recognize distance (tele) 37 Identify distance (wide) 8.3 Identify distance (tele) 19	16.7 m 37.9 m	Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 60 °C 0 - 95%
	8.3 m 19 m	Weight & dimensions	
	1.2 m	Width Depth Height Weight	90.4 mm 244.1 mm 90.4 mm 820 g
		Packaging data	
		Package weight	1.13 kg
		Packaging content	
		Number of cameras *	1

