

Dahua Technology WizSense DH-IPC-HFW2841SP-S-0280B cámara de vigilancia Bala (forma) Cámara de seguridad IP Exterior 2688 x 1520 Pixeles Pared

Marca: Dahua Technology Familia de productos: Código del producto: DH-IPC-

WizSense HFW2841SP-S-0280B

Nombre del producto : DH-IPC-HFW2841SP-S-0280B

Dahua Technology WizSense DH-IPC-HFW2841SP-S-0280B. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 95°, Ángulo de visión del objetivo, vertical: 52°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"). Distancia de detección: 63.6 m, Distancia de observación: 25.4 m, Distancia de reconocimiento: 12.7 m

Performance		Video	
Type * Placement supported *	IP security camera Outdoor	Gain control type Privacy masking	Auto/Manual ✓
Connectivity technology * Wide Dynamic Range (WDR)	Wired ✓	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Day/night mode	✓	Bit rate	12 kbps - 6144 kbps
Dynamic range	120 dB	Back Light Compensation (BLC)	✓
Design		Highlight Compensation (HLC)	✓
Form factor *	Bullet	Region of Interest (ROI) encoding	✓
Mounting type *	Wall	Audio	
Product colour * Housing material International Protection (IP) code	White Metal IP67	Audio formats supported Signal-to-Noise Ratio (SNR) Built-in microphone	G.711 A-law, G.726, PCM 56 dB ✓
Camera		Network	
Camera pan control	✓	Ethernet LAN *	1
Camera tilt control	✓	Ethernet interface type	Fast Ethernet
Minimum illumination	0 lx	, , , , , , , , , , , , , , , , , , ,	IPv4; IPv6; HTTP; TCP; UDP; ARP;
Angle of rotation Lens viewing angle, horizontal	360° 95°	Supported network protocols	RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP
Lens viewing angle, vertical	52°	Wi-Fi *	X
Lens viewing angle, diagonal	114°	Bluetooth *	×
Tilt angle range	0 - 90°	Number of users	6 user(s)
Pan range	0 - 360° Auto, Manual, Natural, Outdoor,	Storage	
White balance	Regional custom, Street lamp	Built-in HDD *	×
Camera shutter type	Electronic	Card reader integrated	,
Camera shutter speed	1/3 - 1/100000 s	Compatible memory cards	MicroSD (TransFlash)
Adjustment shutter speed Number of Privacy masking areas	Auto/Manual 4	Maximum memory card size	256 GB
, ,	4	Internal memory	128 MB
Image sensor		ROM capacity	128 MB
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Ports & interfaces	
Progressive scan Sensor type *	✓ CMOS	Ethernet LAN (RJ-45) ports	1
	CMO3	Security	
Lens system	62.6	Video motion detection	✓
Detect distance Observe distance	63.6 m 25.4 m	Mirror	✓
Recognize distance	12.7 m	Management features	
Identify distance	6.4 m	Web browser	1
Minimum aperture number	1.6	MEN NIOMPEI	✓

Lens system		Power	
Fixed focal length	2.8 mm	Power source type *	DC, PoE
Closest focusing distance	0.9 m	Power consumption (typical)	2.5 W
Night vision		Power consumption (max)	4.2 W
Night vision *	✓	Power consumption (Power over Ethernet (PoE))	3.3 W
Night vision distance	30 m	DC output voltage	12
LED type Number of illumination LEDs	IR 1	Operational conditions	
	1	Operating temperature (T-T)	-40 - 60 °C
Video		Storage temperature (T-T)	-40 - 60 °C
Maximum resolution *	2688 x 1520 pixels	Operating relative humidity (H-H)	0 - 95%
Total megapixels *	4 MP	System requirements	
Video compression formats	H.264, H.264B, H.264H, H.265, M- JPEG	Mobile operating systems supported	Android, iOS
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520	Weight & dimensions	
		Width	166.2 mm
		Depth	70 mm
		Height	70 mm
Video recording	✓	Weight	480 g
Frame rate	30 fps	Packaging data	
Video streaming	✓		F00 -
Noise reduction	✓	Package weight	590 g
Noise reduction technology	3D noise reduction	Packaging content	
		Number of cameras *	1

