



Dahua Technology WizMind DH-IPC-HDW5541TP-ZE cámara de vigilancia Torreta Interior y exterior 2592 x 1944 Píxeles Techo

Marca : Dahua Technology

Familia de productos:
WizMind

Código del producto: DH-IPC-HDW5541TP-ZE

Nombre del producto : DH-IPC-HDW5541TP-ZE

Dahua Technology WizMind DH-IPC-HDW5541TP-ZE. Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico, Rango dinámico: 120 Db. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Torreta. Iluminación mínima: 0.0005 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 100 - 28°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Intervalo de longitud focal: 2.7 - 13.5 mm, Distancia de detección (angular): 64 m, Distancia de detección (tele): 212 m

Performance		Video	
Placement supported *	Indoor & outdoor	Noise reduction	✓
Connectivity technology *	Wired	Noise reduction technology	3D noise reduction
Wide Dynamic Range (WDR)	✓	Gain control type	Auto/Manual
Day/night mode	✓	Privacy masking	✓
Dynamic range	120 dB	Image stabilizer	✓
Design		Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Form factor *	Turret	Bit rate	19 - 8192
Mounting type *	Ceiling	Back Light Compensation (BLC)	✓
Product colour *	White	Highlight Compensation (HLC)	✓
Housing material	Metal, Plastic	Digital Wide Dynamic Range (DWDR)	✓
International Protection (IP) code	IP67	Region of Interest (ROI) encoding	✓
Camera		Audio	
Minimum illumination	0.0005 lx	Audio formats supported	G.711 A-law, G.711 µ-law, G.723, G.726, PCM
Angle of rotation	360°	Built-in microphone	✓
Lens viewing angle, horizontal	100 - 28°	Network	
Lens viewing angle, vertical	72 - 21°	Ethernet LAN *	✓
Lens viewing angle, diagonal	133 - 35°	Ethernet interface type	Fast Ethernet
Tilt angle range	0 - 78°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Pan range	0 - 360°		
White balance	Auto, Manual, Natural, Outdoor, Street lamp		
Camera shutter type	Electronic	Wi-Fi *	✗
Camera shutter speed	1/3 - 1/100000 s	Bluetooth *	✗
Adjustment shutter speed	Auto/Manual	Number of users	20 user(s)
Number of Privacy masking areas	8	Storage	
Image sensor		Built-in HDD *	✗
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Card reader integrated	✓
Progressive scan	✓	Compatible memory cards	MicroSD (TransFlash)
Sensor type *	CMOS	Maximum memory card size	256 GB
Lens system		Internal memory	1000 MB
Number of lenses *	1	ROM capacity	128 MB
Focal length range	2.7 - 13.5 mm	Ports & interfaces	
Maximum aperture number	1.5	Ethernet LAN (RJ-45) ports	1
Detect distance (wide)	64 m	Security	
Detect distance (tele)	212 m	Video motion detection	✓
Observe distance (wide)	25.6 m		
Observe distance (tele)	84.8 m		
Recognize distance (wide)	12.8 m		
Recognize distance (tele)	42.4 m		
Identify distance (wide)	6.4 m		

Lens system		Security	
Identify distance (tele)	21.2 m	Mirror	✓
Closest focusing distance	0.8 m	Network access storage (NAS)	✓
Night vision		Management features	
Night vision *	✓	Web browser	✓
Night vision distance	40 m	Power	
LED type	IR	Power source type *	DC, PoE
Number of illumination LEDs	2	Power consumption (typical)	1.9 W
Video		Power consumption (Power over Ethernet (PoE))	2.2 W
Maximum resolution *	2592 x 1944 pixels	DC output voltage	12
Total megapixels *	5 MP	Operational conditions	
Video compression formats	H.264, H.264B, H.264H, H.265	Operating temperature (T-T)	-30 - 60 °C
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2592 x 1944, 2668 x 1512	Storage temperature (T-T)	-40 - 60 °C
Supported video modes	720p, 1080p	System requirements	
Frame rate	60 fps	Mobile operating systems supported	Android, iOS
Video streaming	✓	Weight & dimensions	
		Height	108.3 mm
		Diameter	12.2 cm
		Weight	740 g
		Packaging data	
		Package weight	910 g
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date