Dahua Technology TPC-BF1241-B7F8-DW-S2 Bala (forma) Cámara de seguridad IP Interior y exterior 2336 x 1752 Pixeles Pared

Marca : Dahua Technology

Código del producto: DHI-TPC-BF1241-B7F8-DW-S2

Nombre del producto : TPC-BF1241-B7F8-DW-S2

Dahua Technology TPC-BF1241-B7F8-DW-S2. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Pared, Color del producto: Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.005 Lux, Ángulo del campo de visión (FOV) (módulo térmico): 24 x 18°, Ángulo de visión del objetivo, horizontal: 33.4°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"), Tipo de sensor (módulo térmico): Vanadium Oxide Uncooled Focal Plane Arrays. Intervalo de longitud focal: 8 mm, Distancia más cercana de enfoque: 2.5 m, Longitud focal fija (módulo térmico): 7 mm

Performance		Video	
Type *	IP security camera	Back Light Compensation (BLC)	1
Placement supported *	Indoor & outdoor	Highlight Compensation (HLC)	1
Connectivity technology *	Wired	Digital Wide Dynamic Range	
Thermal module	1	(DWDR)	
Alarm input/output	1	Audio	
Thermal sensitivity (NETD)	40 mK	Audio input channels	1 channels
Design		Audio output channels	1 channels
Form factor *	Bullet	Audio formats supported	G.711
Mounting type *	Wall	Network	
Product colour *	White	Ethernet LAN *	1
International Protection (IP) code	IP67		HTTPS; HTTP; TCP; ARP; RTSP; RTP;
Camera		Supported network protocols	UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; SNMP; QoS;
Minimum illumination	0.005 lx		UPnP; NTP
Field of view (FOV) angle (thermal module)	24 x 18°	Wi-Fi *	×
Lens viewing angle, horizontal	33.4°	Bluetooth *	×
Lens viewing angle, vertical	25°	Storage	
White balance	Auto, Indoor, Manual, Natural,	Compatible memory cards	MicroSD (TransFlash)
Camera shutter speed	Outdoor, Street lamp 1/30,000 -1	Maximum memory card size	256 GB
	1/50,000 -1	Ports & interfaces	
Image sensor	25.4/2.7 mm $(1.72.7")$	Ethernet LAN (RJ-45) ports	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7") Vanadium Oxide Uncooled Focal	Ethernet LAN (RJ-45) ports Security	1
-	25.4 / 2.7 mm (1 / 2.7") Vanadium Oxide Uncooled Focal Plane Arrays		1
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal	Vanadium Oxide Uncooled Focal	Security	
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module)	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels	Security Alarm input channels	1
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type *	Vanadium Oxide Uncooled Focal Plane Arrays	Security Alarm input channels Alarm output channels	1
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS	Security Alarm input channels Alarm output channels Power	1 1
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses *	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1	Security Alarm input channels Alarm output channels Power Power source type * Power consumption (typical) Power consumption (max)	1 1 DC, PoE 8 W 14 W
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS	Security Alarm input channels Alarm output channels Power Power source type * Power consumption (typical) Power consumption (max) DC output voltage	1 1 DC, PoE 8 W
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 1 8 mm	Security Alarm input channels Alarm output channels Power Power source type * Power consumption (typical) Power consumption (max)	1 1 DC, PoE 8 W 14 W
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m	Security Alarm input channels Alarm output channels Power Power source type * Power consumption (typical) Power consumption (max) DC output voltage	1 1 DC, PoE 8 W 14 W
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm	Security Alarm input channels Alarm output channels Power Power Power consumption (typical) Power consumption (max) DC output voltage Operational conditions Operating temperature (T-T) Storage temperature (T-T)	1 1 DC, PoE 8 W 14 W 12 -30 - 50 °C -30 - 70 °C
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance Fixed focal length (thermal module)	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm	Security Alarm input channels Alarm output channels Alarm output channels Power Power source type * Power consumption (typical) Power consumption (max) DC output voltage Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	1 1 2 DC, PoE 8 W 14 W 12 -30 - 50 °C
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance Fixed focal length (thermal module) Aperture number (thermal module)	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm	Security Alarm input channels Alarm output channels Power Power Power consumption (typical) Power consumption (max) DC output voltage Dperational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	1 1 2 DC, PoE 8 W 14 W 12 -30 - 50 °C -30 - 70 °C 0 - 95%
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance Fixed focal length (thermal module) Aperture number (thermal module) Night vision	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm 1	Security Alarm input channels Alarm output channels Alarm output channels Power Power consumption (typical) Power consumption (max) Do output voltage Deperational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	1 1 1 DC, PoE 8 W 14 W 12 -30 - 50 °C -30 - 70 °C 0 - 95%
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance Fixed focal length (thermal module) Aperture number (thermal module) Might vision Night vision *	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm 1	Security Alarm input channels Alarm output channels Alarm output channels Power Power consumption (typical) Power consumption (max) DC output voltage Poperational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions Width Depth	1 1 1 DC, PoE 8 W 14 W 12
Optical sensor size Sensor type (thermal module) Effective sensor resolution (thermal module) Sensor type * Lens system Number of lenses * Focal length range Maximum aperture number Closest focusing distance Fixed focal length (thermal module) Aperture number (thermal module) Aperture number (thermal module) Night vision * Video	Vanadium Oxide Uncooled Focal Plane Arrays 256 x 192 pixels CMOS 1 8 mm 2 2.5 m 7 mm 1 1 1	Security Alarm input channels Alarm output channels Alarm output channels Power Power consumption (typical) Power consumption (max) Do output voltage Deperational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Weight & dimensions	1 1 1 DC, PoE 8 W 14 W 12 -30 - 50 °C -30 - 70 °C 0 - 95%

Video

Noise reduction

Noise reduction technology

2D noise reduction, 3D noise reduction

Packaging data

Packaging content		
Package weight	1.3 kg	
Package height	279 mm	
Package depth	187 mm	
Package width	138 mm	

Number of cameras *

1



8435280913962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.