



Dahua Technology Lite DH-HAC-HDBW1200EAN cámara de vigilancia Domo Cámara de seguridad CCTV Interior y exterior 1920 x 1080 Pixeles Techo/pared/Tubo

Marca : Dahua Technology

Familia de productos: Lite

Código del producto: DH-HAC-HDBW1200EAN

Nombre del producto : DH-HAC-HDBW1200EAN

Dahua Technology Lite DH-HAC-HDBW1200EAN. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Negro, Blanco, Factor de forma: Domo. Iluminación mínima: 0.001 Lux, Ángulo de rotación: 355°, Ángulo de visión del objetivo, horizontal: 102°. Tipo de sensor: CMOS. Distancia de detección: 50.9 m, Distancia de observación: 20.3 m, Distancia de reconocimiento: 10.2 m

Performance		Night vision	
Type *	CCTV security camera	Night vision *	✔
Placement supported *	Indoor & outdoor	Night vision distance	40 m
Connectivity technology *	Wired	LED type	IR
Wide Dynamic Range (WDR)	✔	Number of illumination LEDs	3
Day/night mode	✔	Video	
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B; UL: UL62368-1 + CAN/CSA C22.2 No. 62368-1-14	Maximum resolution *	1920 x 1080 pixels
		Total megapixels *	2 MP
		Frame rate	30 fps
		Analog signal format system	NTSC
		Noise reduction	✔
Design		Noise reduction technology	3D noise reduction
		Gain control type	Auto
		Privacy masking	✔
		Back Light Compensation (BLC)	✔
		Highlight Compensation (HLC)	✔
		Digital Wide Dynamic Range (DWDR)	✔
		Smart IR	✔
		Audio	
		Signal-to-Noise Ratio (SNR)	65 dB
		Ports & interfaces	
		BNC output ports	1
		Power	
		Power source type *	DC
		Power consumption (max)	2.8 W
		DC output voltage	12
Image sensor		Operational conditions	
Progressive scan	✔	Operating temperature (T-T)	-40 - 60 °C
Sensor type *	CMOS	Storage temperature (T-T)	-40 - 60 °C
Lens system		Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Weight & dimensions	
		Height	89.1 mm
		Diameter	11.2 cm
Detect distance	50.9 m	Weight	440 g
Observe distance	20.3 m	Packaging data	
Recognize distance	10.2 m	Package weight	620 g
Maximum aperture number	2		
Identify distance	5.1 m		
Fixed focal length	3.6 mm		
Closest focusing distance	0.5 m		

Packaging content

Number of cameras *	1
---------------------	---

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date