



DELL N-Series N3224P Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) 1U Negro

Marca : DELL

Familia de productos: N-Series

Código del producto: N3224P_1.1



Nombre del producto : N3224P

- N3224P-ON: 1RU, 24 puertos PoE RJ45 1 G con 802.3at (30 W)
 - Transferencia combinada de 400 G con hasta 12 miembros
 - Enlaces de subida 10 G para agregación
 - Ideal para redes de campus de medianas y grandes empresas, así como implementaciones para minoristas
- 24 x RJ-45, 4x10G SFP+, 2x100G QSFP28, PoE 30W

[DELL N-Series N3224P Gestionado L2 Gigabit Ethernet \(10/100/1000\) Energía sobre Ethernet \(PoE\) 1U Negro:](#)

Inicie sus redes de acceso de campus

Switches PoE Multi-Gig y Multi-Gig 802.3bt de 90 W con 8, 24 y 48 puertos, diseñados ex profeso, para ejecutar cargas de trabajo modernas y mejorar la productividad de los empleados. DELL N-Series N3224P. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 24, Puerto de consola: MicroUSB. Bidireccional completo (Full duplex), Estándares de red: IEEE 802.3at. Energía sobre Ethernet (PoE). Montaje en rack, Factor de forma: 1U

Management features		Design	
Switch type *	Managed	Stackable *	✓
Switch layer	L2	Form factor	1U
Quality of Service (QoS) support	✓	Product colour	Black
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	24	Power source *	AC
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included *	✓
SFP+ module slots quantity	4	AC input voltage	100 - 240 V
Fiber optic connector	SFP+	AC input frequency	50 - 60 Hz
Console port	Micro-USB	Output voltage	125 V
QSFP28 ports quantity	2	Output current	15 A
Network		Power cable length	3 m
Networking standards *	IEEE 802.3at	Power cable connector 1	NEMA 5-15P
10G support *	✓	Power cable connector 2	C13 coupler
Port mirroring	✓	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Policy-based routing	✓	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	0 - 45 °C
Link aggregation	✓	Storage temperature (T-T)	-40 - 70 °C
Auto MDI/MDI-X	✓	Operating relative humidity (H-H)	5 - 95%
Spanning tree protocol	✓	Storage relative humidity (H-H)	5 - 95%
Auto-sensing	✓	Weight & dimensions	
Auto-negotiation	✓	Width	434 mm
Design		Depth	400 mm
Rack mounting *	✓	Height	43.5 mm
		Packaging content	
		Cables included	AC

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date