



Dahua Technology XVR1B04-I videgrabadora digital Negro

Marca : Dahua Technology

Código del producto: XVR1B04-I

Nombre del producto : XVR1B04-I

Dahua Technology XVR1B04-I. Color del producto: Negro, Máxima resolución de video: 1920 x 1080 Pixeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Canales de entrada de vídeo: 5 canales. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP, HTTPS, TCP/IP, IPv4/IPv6, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE,..., Número de usuarios: 128 usuario(s). Interfaz del HDD: SATA, Capacidad máxima del HDD: 6 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V, Consumo energético: 7 W

Performance		Ports & interfaces	
Maximum video resolution	1920 x 1080 pixels	USB 2.0 ports quantity	2
Video compression formats	H.264, H.264+, H.265, H.265+	Network	
Audio formats supported	G.711 A-law, G.711 µ-law, PCM	Ethernet LAN	✓
Internal	✗	Ethernet interface type	Fast Ethernet
Backup function	✓	Ethernet LAN (RJ-45) ports	1
Video capturing speed	30 fps	Supported network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, 3G/4G, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, P2P, IP Search
Video loss detection	✓		
Video motion detection	✓	Number of users	128 user(s)
Channels quantity	4 channels	Hard drive	
Product colour *	Black	Number of HDDs supported	1
Playback modes	Backup selection, Full screen, Next, Pause, Play, Previous, Repeat, Shuffle, Slow, Stop, Zoom	HDD interface	SATA
Analog signal format system	NTSC, PAL	Maximum HDD capacity	6 TB
Operating system installed	Embedded LINUX	Processor	
Audio system	2-way	Built-in processor	✓
Audio input channels	1 channels	Power	
Audio output channels	1.0 channels	Power supply type	DC
Maximum frame rate	60 fps	DC voltage	12 V
USB connectivity	✓	Power consumption (typical)	7 W
Multi-display supported	✓	Weight & dimensions	
Multi-display modes	1, 4, 6	Width	198 mm
Motion sensor	✓	Depth	202.9 mm
Video streaming	✓	Height	41.5 mm
Dual stream support	✓	Weight	570 g
Bit rate	32 Kbit/s	Packaging data	
PTZ control	✓	Package weight	1.08 kg
Rack capacity	1U	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	-10 - 45 °C
Video input channels	5 channels	Operating relative humidity (H-H)	0 - 90%
HDMI ports quantity	1	Storage temperature (T-T)	-20 - 70 °C
VGA (D-Sub) output ports	1	Storage relative humidity (H-H)	0 - 90%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date