

Dahua Technology DH-SD49225DB-HC cámara de vigilancia Esférico Cámara de seguridad CCTV Exterior 1920 x 1080 Pixeles Techo

Marca : Dahua Technology Código del producto: DH-SD49225DB-HC

Nombre del producto: DH-SD49225DB-HC

Dahua Technology DH-SD49225DB-HC. Tipo: Cámara de seguridad CCTV, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Esférico. Ángulo de visión del objetivo, horizontal: 60.6 - 3.2°, Ángulo de visión del objetivo, vertical: 34.1 - 1.8°, Ángulo de visión de la lente, diagonal: 69.4 - 3.7°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Zoom óptico: 25x, Zoom digital: 16x, Distancia de detección: 1655.2 m

Performance		Lens system	
Type *	CCTV security camera	Closest focusing distance	0.1 m
Placement supported *	Outdoor Wired	Night vision	
Connectivity technology *		Night vision *	✓
PTZ control		Night vision distance	100 m
PTZ modes	5 Pattern, 8 Tour, Auto scan, Preset point	LED type	IR
PTZ protocols	DH-SD	Number of illumination LEDs	6
Preset points	✓	Video	
Wide Dynamic Range (WDR)	✓	Maximum resolution *	1920 x 1080 pixels
Day/night mode	✓	Total megapixels *	2 MP
Alarm input/output	✓	Supported graphics resolutions	704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Dynamic range	120 dB	Frame rate	60 fps
Design		Analog signal format system	PAL
Form factor *	Spherical	Noise reduction	✓
Mounting type * Product colour *	Ceiling White	Noise reduction technology	2D noise reduction, 3D noise reduction
International Protection (IP) code	IP66	Gain control type	Auto/Manual
Camera		Privacy masking	✓
Camera pan control	1	Back Light Compensation (BLC)	✓
Camera tilt control	•	Highlight Compensation (HLC)	✓
Minimum illumination	0 lx	Audio	
Lens viewing angle, horizontal	60.6 - 3.2°	Audio input channels	1 channels
Lens viewing angle, vertical	34.1 - 1.8°	Audio output channels	1 channels
Lens viewing angle, diagonal	69.4 - 3.7°	Signal-to-Noise Ratio (SNR)	50 dB
Tilt angle range	-15 - 90° 200 °/sec	Network	
Tilt preset speed		Ethernet LAN *	×
Tilt manual speed	0.1 - 120 °/sec	Wi-Fi *	×
Pan range Pan preset speed	0 - 360° 240 °/sec	Bluetooth *	×
Pan manual speed	0.1 - 200 °/sec	Storago	
Auto flip	✓	Storage	
White balance	Auto, Indoor, Manual, Natural, Outdoor, Sodium lamp, Street lamp	Built-in HDD * Internal memory	X 256 MB
Camera shutter type	Electronic	ROM capacity	128 MB
Camera shutter speed	1/3 - 1/30000 s	Ports & interfaces	
Image sensor	25 4 / 2 0 /1 / 2 0 2	RS-485 ports BNC output ports	1 1
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Power	
Progressive scan Sensor type *	CMOS	Power source type *	DC
Sensor type	CMIO3	Power consumption (typical)	10 W

Lens system		Power
Zoom capability Optical zoom	✓ 25x	Power consumption (max) 22 W DC output voltage 12
Digital zoom	16x	Operational conditions
Detect distance Observe distance	stance 653.8 m distance 331 m th range 4.8 - 120 mm aperture number 3.5 stance 165.5 m	Operating temperature (T-T) -40 - 70 °C Operating relative humidity (H-H) 0 - 95%
Recognize distance Focal length range		Weight & dimensions
Auto focus Maximum aperture number Identify distance		Height 269.9 mm Diameter 16 cm Weight 3 kg
Minimum aperture number		Packaging data
		Package weight 4.2 kg
		Packaging content
		Number of cameras * 1

