

Dahua Technology Lite DH-HAC-HDW1209TLQN-LED cámara de vigilancia Domo Cámara de seguridad IP Exterior 1920 x 1080 Pixeles Pared



Marca : Dahua Technology Familia de productos: Lite Código del producto: DH-HAC-HDW1209TLQN-LED

Nombre del producto : DH-HAC-HDW1209TLQN-LED

Dahua Technology Lite DH-HAC-HDW1209TLQN-LED. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Pared, Color del producto: Blanco, Factor de forma: Domo. Iluminación mínima: 0.01 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 106°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Número de píxeles efectivos (A x V): 1920 x 1080 Pixeles. Distancia de detección: 43.9 m, Distancia de observación: 17.5 m, Distancia de reconocimiento: 8.8 m

Performance		Lens system	
Type *	pe * IP security camera	Identify distance (2.8mm lens)	4.4 m
Certification 47 FCC Part 15 subpartB, ANSI		Night vision	
		Night vision *	✓
	CE (EN55032, EN55024, EN50130-4,EN60950-1) FCC (CFR	Night vision distance	20 m
		LED type	IR
		Number of illumination LEDs	1
Design		Video	
Form factor *	Dome	Maximum resolution *	1920 x 1080 pixels
Mounting type *	Wall	Total megapixels *	2 MP
Product colour *	White	Supported video modes Frame rate	720p, 1080p 30 fps
Housing material	Metal, Plastic	Noise reduction	50 1μs ✓
International Protection (IP) code	IP67	Noise reduction Noise reduction technology	2D noise reduction
Camera		Gain control type	Auto/Manual
Minimum illumination	0.01 lx	Privacy masking	✓
Angle of rotation	360°	Back Light Compensation (BLC)	·
Lens viewing angle, horizontal	106°	Digital Wide Dynamic Range	
Lens viewing angle, vertical	56.5°	(DWDR)	✓
Tilt angle range	126.2° 0 - 78° 0 - 360°	Network	
		Ethernet LAN *	×
Pan range White balance	Auto, Manual	Wi-Fi *	×
Camera shutter type	Electronic	Bluetooth *	×
Number of Privacy masking areas	8	Ports & interfaces	
Image sensor		BNC output ports	1
Number of sensors	1	Microphone in	✓
Optical sensor size		Security	
Progressive scan	✓ CMOS	Mirror	✓
Sensor type * Number of effective pixels (H x V)	1920 x 1080 pixels	Power	
Lens system	, -	Power source type *	DC
Number of lenses *	1	Power consumption (max)	3.1 W
Detect distance	43.9 m	DC output voltage	12
Observe distance	17.5 m	Operational conditions	
Recognize distance	8.8 m	Operating temperature (T-T)	-40 - 60 °C
Maximum aperture number	1.6	Storage temperature (T-T)	0 - 95 °C
Identify distance	4.4 m	Operating relative humidity (H-H)	-40 - 60%
Fixed focal length	2.8 mm	Storage relative humidity (H-H)	0 - 95%

Lens system		Weight & dimensions	
Closest focusing distance	0.7 m	Width	91.4 mm
Detect distance (2.8mm lens)	43.9 m	Diameter	9.71 cm
Observe distance (2.8mm lens) Recognize distance (2.8mm lens)	17.5 m 8.8 m	Weight	210 g
		Packaging data	
		Package weight	280 g
		Packaging content	
		Number of cameras *	1
		Technical details	
		Iris	1

