



Dahua Technology XVR5104HS-4KL-I3 Negro

Marca : Dahua Technology

Código del producto: DH-XVR5104HS-4KL-I3

Nombre del producto : XVR5104HS-4KL-I3



Dahua Technology XVR5104HS-4KL-I3. Color del producto: Negro, Máxima resolución de video: 3840 x 2160 Pixeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Canales de entrada de video: 4 canales, Salida de audio: 1 RCA. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Interfaz del HDD: SATA, Capacidad máxima del HDD: 16 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V, Consumo energético: 7 W

Desempeño	
Máxima resolución de video	3840 x 2160 Pixeles
Formatos de compresión de video	H.264, H.264+, H.265, H.265+
Formatos de audio soportados	G.711 A-law, G.711 μ-law, PCM
Función de copia de seguridad	✔
Velocidad de captura de vídeo	30 fps
Velocidad de captura ed video (PAL)	25 fps
Velocidad de captura ed video (NTSC)	30 fps
Detección de perdida de video	✔
Detección de movimiento en video	✔
Cantidad de canales	4 canales
Color del producto *	Negro
Sistema operativo instalado	LINUX incrustado
Contro PTZ	✔
Capacidad del rack	1U
Certificación	FCC: Part 15 Subpart B CE: CE-LVD:
	EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024
Puertos e Interfaces	
Canales de entrada de vídeo	4 canales
puertos de entrada BNC	4
Número de puertos HDMI	1
Entrada de audio	1
Salida de audio	1 RCA
Cantidad de puertos USB 2.0	2
Puertos RS-485	1
Red	
Ethernet	✔
Tipo de interfaz ethernet	Ethernet rápido
Puertos Ethernet LAN (RJ-45)	1
Protocolos de red compatibles	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Disco duro	
Número de HDDs soportados	1
Interfaz del HDD	SATA
Capacidad máxima del HDD	16 TB
Control de energía	
Tipo de fuente de alimentación	CC
Voltaje CD	12 V
Consumo energético	7 W
Peso y dimensiones	
Ancho	260 mm
Profundidad	237.9 mm
Altura	47.6 mm
Peso	530 g
Empaquetado de datos	
Ancho del paquete	333 mm
Largo del paquete	315 mm
Alto del paquete	89 mm
Peso del paquete	1.07 kg
Exhibición	
Pantalla incorporada	✘
Condiciones ambientales	
Intervalo de temperatura operativa (T-T)	-10 - 55 °C
Intervalo de humedad relativa para funcionamiento	10 - 90%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-NOV-2023. Prints or copies of Information are only valid on the printed Publication date