



Dahua Technology XVR5104HS-4KL-I3 Negro

Marca : Dahua Technology

Código del producto: DH-XVR5104HS-4KL-I3

Nombre del producto : XVR5104HS-4KL-I3

Dahua Technology XVR5104HS-4KL-I3. Color del producto: Negro, Máxima resolución de video: 3840 x 2160 Pixeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Canales de entrada de vídeo: 4 canales, Salida de audio: 1 RCA. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. Interfaz del HDD: SATA, Capacidad máxima del HDD: 16 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V, Consumo energético: 7 W



Performance		Network	
Maximum video resolution	3840 x 2160 pixels	Ethernet interface type	Fast Ethernet
Video compression formats	H.264, H.264+, H.265, H.265+	Ethernet LAN (RJ-45) ports	1
Audio formats supported	G.711 A-law, G.711 μ-law, PCM	Supported network protocols	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P
Backup function	✓		
Video capturing speed	30 fps		
Video capturing speed (PAL)	25 fps	Hard drive	
Video capturing speed (NTSC)	30 fps	Number of HDDs supported	1
Video loss detection	✓	HDD interface	SATA
Video motion detection	✓	Maximum HDD capacity	16 TB
Channels quantity	4 channels	Power	
Product colour *	Black	Power supply type	DC
Operating system installed	Embedded LINUX	DC voltage	12 V
PTZ control	✓	Power consumption (typical)	7 W
Rack capacity	1U	Weight & dimensions	
Certification	FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024	Width	260 mm
		Depth	237.9 mm
		Height	47.6 mm
		Weight	530 g
Ports & interfaces		Packaging data	
Video input channels	4 channels	Package width	333 mm
BNC input ports	4	Package depth	315 mm
HDMI ports quantity	1	Package height	89 mm
Audio input	1	Package weight	1.07 kg
Audio output	1 RCA	Display	
USB 2.0 ports quantity	2	Built-in display	✗
RS-485 ports	1	Operational conditions	
Network			
Ethernet LAN	✓		

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 90%



6939554930430

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date