

TP-Link TL-SG108S No administrado Gigabit Ethernet (10/100/1000) Negro

Marca : TP-Link Código del producto: TL-SG108S V1

Nombre del producto: TL-SG108S




TP-Link TL-SG108S. Tipo de interruptor: No administrado. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 4000 entradas, Capacidad de conmutación: 16 Gbit/s. Estándares de red: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Montaje de pared



Management features		Performance	
Switch type *	Unmanaged	Plug and Play	✓
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		Power source *	DC
Basic switching RJ-45 Ethernet ports quantity *	8	Power supply included * Input current	✓ 0.6 A
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Input voltage	9 V
Gigabit Ethernet (copper) ports quantity	8	Output voltage Power consumption (max)	9 V 3.3 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE	Power over Ethernet (PoE) *	×
10G support *	802.3ab, IEEE 802.3u, IEEE 802.3x	Operational conditions	
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Cable types supported Full duplex	Cat3, Cat4, Cat5, Cat5e	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90% 5 - 90%
Flow control support	√	Weight & dimensions	
Auto MDI/MDI-X	✓	Width	158 mm
Auto-negotiation	✓	Depth	100.6 mm
Data transmission		Height	25.4 mm
Switching capacity *	16 Gbit/s	Packaging content	
Forwarding rate	11.9 Mpps	Cables included	AC
MAC address table *	4000 entries	Quick start guide	✓
Store-and-forward	✓	Packaging data	
Jumbo frames support	✓	AC adapter included	✓
Jumbo frames Packet buffer memory	16000 1.5 MB	Package type	Вох

Security		Packaging data	
IGMP snooping	✓	Rubber feet	✓
Design	ck mounting * X duct colour Black D indicators Il mountable	Package width Package depth	191 mm 130 mm
Rack mounting * Product colour		Package height Package weight	92 mm 520 g
LED indicators Wall mountable		Certificates	
		Certification Logistics data	CE, FCC ,RoHS
		Harmonized System (HS) code	85176990









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.