

GIGABYTE B760 AORUS ELITE AX placa base Intel B760 LGA 1700 ATX

Marca : GIGABYTE

Código del producto: B760 AORUS ELITE AX

Nombre del producto : B760 AORUS ELITE AX

GIGABYTE B760 AORUS ELITE AX. Fabricante de procesador: Intel, Socket de procesador: LGA 1700, Procesador compatible: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... tipos de memoria compatibles: DDR5-SDRAM, Memoria interna máxima: 192 GB, Tipo de ranuras de memoria: DIMM. Interfaces de disco de almacenamiento soportados: M.2, SATA III, Tipos de unidades de almacenamiento admitidas: HDD & SSD, Niveles RAID: 0, 1, 5, 10. Máxima resolución: 4096 x 2304 Pixeles. Tipo de conector USB: USB tipo A, USB Tipo C



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	Microphone in	✓
Processor socket *	LGA 1700	S/PDIF out port	✓
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold	Digital audio optical out	1
		Wi-Fi-AP antenna jack	2
Maximum number of SMP processors	1	USB connector type	USB Type-A, USB Type-C
Supported processor sockets	LGA 1700	Network	
Memory		Ethernet LAN	✓
Supported memory types *	DDR5-SDRAM	Ethernet interface type	2.5 Gigabit Ethernet
Number of memory slots *	4	LAN controller	Realtek RTL8125
Memory slots type	DIMM	Wi-Fi *	✓
Memory channels	Dual-channel	Top Wi-Fi standard	Wi-Fi 6E (802.11ax)
ECC compatibility	ECC & Non-ECC	Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)
Supported memory clock speeds	4000,4800,5200,5400,5600,5800,6000,6200,6400,6600,6800,7000,7200,7400,7600,7800 MHz	WLAN controller model	Realtek RTL8852CE
Supported memory clock speed (max)	7600 MHz	Bluetooth	✓
Maximum internal memory *	192 GB	Bluetooth version	5.3
Unbuffered memory	✓	Features	
Storage controllers		Motherboard chipset *	Intel B760
Supported storage drive types	HDD & SSD	Audio chip	Realtek ALC897
Supported storage drive interfaces *	M.2, SATA III	Audio output channels *	7.1 channels
Number of HDDs supported	4	Product colour	Black
Number of storage drives supported	7	PC health monitoring	Fan, Temperature, Voltage, Water cooling
RAID support	✓	Component for *	PC
RAID levels	0, 1, 5, 10	Motherboard form factor *	ATX
Graphics		Motherboard chipset family *	Intel
Parallel processing technology support *	Not supported	Power source type	ATX
Maximum resolution	4096 x 2304 pixels		
HDCP	✓		
Discrete graphics support	✓		


Internal I/O		Features	
USB 2.0 connectors *	2	Windows operating systems supported	Windows 10 x64, Windows 11 x64
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	<b>Expansion slots</b>	
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	PCI Express x16 (Gen 3.x) slots	2
Number of SATA III connectors *	4	PCI Express x16 (Gen 4.x) slots	1
S/PDIF out connector	✓	Number of M.2 (M) slots	3
Front panel audio connector	✓	<b>BIOS</b>	
Front panel connector	✓	BIOS type *	UEFI AMI
ATX Power connector (24-pin)	✓	BIOS memory size	256 Mbit
Number of EATX power connectors	2	ACPI version	5.0
CPU fan connector	✓	Clear CMOS jumper	✓
Number of chassis fan connectors	4	Desktop Management Interface (DMI) version	2.7
Peripheral (Molex) power connectors (4-pin)	1	System Management BIOS (SMBIOS) version	2.7
EPS power connector (8-pin)	✓	<b>Logistics data</b>	
TPM connector	✓	Country of origin	China
12V power connector	✓	Products per shipping (inner) case	1 pc(s)
RGB LED pin header	✓	<b>Battery</b>	
Rear panel I/O ports		Battery weight	3 g
USB 2.0 ports quantity *	4	Lithium weight per battery	0.07 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Number of battery cells	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
USB 3.2 Gen 2x2 Type-C ports quantity	1	Battery type	CR2032
Ethernet LAN (RJ-45) ports *	1	<b>Packaging data</b>	
HDMI ports quantity *	1	Package width	335 mm
DisplayPorts quantity	1	Package depth	270 mm
Headphone outputs	1	Package height	80 mm
		Package weight	2.16 kg
		<b>Weight &amp; dimensions</b>	
		Width	305 mm
		Depth	244 mm
		Height	35 mm
		<b>Packaging content</b>	
		Cables included	SATA
		Batteries included	✓
		Antenna included	✓
		Bundled software	Norton® Internet Security (OEM version) LAN bandwidth management software
		<b>Technical details</b>	
		Warranty period	3 year(s)



4719331851750



0889523035924



889523035924

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date