

Huawei NetEngine 8000 M1C enrutador Negro, Plata

Marca : Huawei

Familia de productos:
NetEngine

Código del producto:
NETENGINE 8000 M1C

Nombre del producto :
NETENGINE 8000 M1C



Router Huawei para Redes Empresariales 16 puertos SFP+/ 8 puertos SFP / 4 puertos GE
Huawei NetEngine 8000 M1C. Estándares de red: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ad, Capacidad de conmutación: 344 Gbit/s. Versión USB: 3.2 Gen 1 (3.1 Gen 1). Protocolo de ruteo: BGP4, BGP4+, IS-IS, OSPFv2, OSPFv3, RIP, RIP-2. Memoria interna: 8000 MB, Certificación: CISPR32 Class A EN 55032 Class A CISPR24 EN 55024 ETSI EN 300 386 AS/NZS CISPR32 Class A FCC Part.... Color del producto: Negro, Plata, Capacidad del rack: 1U



WAN connection		Features	
Ethernet WAN *	✓	Certification	CISPR32 Class A EN 55032 Class A CISPR24 EN 55024 ETSI EN 300 386 AS/NZS CISPR32 Class A FCC Part 15 Subpart B Class A ICES 003 Class A IEC 61000-3-2 EN 61000-3-2 IEC 61000-3-3 EN 61000-3-3 GB 9254 VCCI-CISPR32 Class A RoHS REACH WEEE IEC 60950-1 EN 60950-1 UL 60950-1 CSA C22.2 No 60950-1 GB 4943.1
DSL WAN *	✗		
SIM card slot *	✗		
3G/4G USB modem compatibility *	✗		
SFP WAN *	✓		
Network			
Networking standards *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ab, IEEE 802.3ad	Design	
Switching capacity	344 Gbit/s	Product colour *	Black, Silver
Static route	✓	Rack mounting	✓
VLAN support	✓	Rack capacity	1U
Management features		Power	
Quality of Service (QoS) support	✓	Power consumption (typical) *	89.21 W
Ports & interfaces		Power source type	AC
Gigabit Ethernet (copper) ports quantity	4	Redundant power supply (RPS) support	✓
SFP module slots quantity	8	Input current	5.5 A
SFP+ module slots quantity	16	Operational conditions	
USB version	3.2 Gen 1 (3.1 Gen 1)	Operating temperature (T-T)	-40 - 65 °C
Protocols		Storage temperature (T-T)	-40 - 70 °C
Routing protocols	BGP4, BGP4+, IS-IS, OSPFv2, OSPFv3, RIP, RIP-2	Operating relative humidity (H-H)	5 - 95%
DHCP client *	✓	Storage relative humidity (H-H)	5 - 100%
DHCP server *	✓	Operating altitude	0 - 4000 m
Security		Non-operating altitude	0 - 5000 m
		Weight & dimensions	
Network address translation (NAT)	✓	Width	444.5 mm

Features		Weight & dimensions	
Internal memory	8000 MB	Depth	442 mm
		Height	220 mm
		Weight	3.9 kg
		Packaging data	
		Package width	550 mm
		Package depth	650 mm
		Package height	175 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date