



Dahua Technology XVR1B04H-I(512G) Negro

Marca : Dahua Technology

Código del producto: DH-XVR1B04H-I-SSD



Nombre del producto : XVR1B04H-I(512G)

Dahua Technology XVR1B04H-I(512G). Color del producto: Negro, Máxima resolución de video: 1920 x 1080 Píxeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm..., Número de usuarios: 128 usuario(s). Interfaz del HDD: SATA, Capacidad máxima del HDD: 6 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V. Ancho: 197 mm, Profundidad: 203.4 mm, Altura: 41.5 mm

Performance		Network	
Maximum video resolution	1920 x 1080 pixels	Ethernet LAN (RJ-45) ports	1
Video compression formats	H.264, H.264+, H.265, H.265+	Supported network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P, IP Search
Audio formats supported	AAC, G.711, PCM	Number of users	128 user(s)
Backup function	✓	Hard drive	
Video motion detection	✓	Number of HDDs supported	1
Playback resolutions supported	1920×1080, 1280×1024, 1280×720	HDD interface	SATA
Channels quantity	4 channels	Maximum HDD capacity	6 TB
Product colour *	Black	Power	
Playback modes	Fast, Next, Pause, Play, Previous, Repeat, Shuffle, Slow, Stop, Zoom	Power supply type	DC
Analog signal format system	NTSC, PAL	DC voltage	12 V
Operating system installed	Embedded LINUX	Weight & dimensions	
PTZ control	✓	Width	197 mm
Rack capacity	1U	Depth	203.4 mm
Certification	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN 50130; EN 55024	Height	41.5 mm
Ports & interfaces		Weight	550 g
BNC input ports	4	Packaging data	
BNC output ports	1	Package width	332 mm
HDMI ports quantity	1	Package depth	240 mm
VGA (D-Sub) output ports	1	Package height	64 mm
Audio input	1	Package weight	1.02 kg
Audio output	1	Packaging content	
USB 2.0 ports quantity	2	Cables included	AC
Network		AC adapter included	✓
Ethernet LAN	✓	Quick start guide	✓
Ethernet interface type	Fast Ethernet	Operational conditions	
		Operating temperature (T-T)	-10 - 45 °C
		Storage temperature (T-T)	-20 - 70 °C

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date