


ASUS Prime H610M-K Intel H610 LGA 1700 Micro ATX

Marca : ASUS

Código del producto: 90MB1GA0-M0EAY0

Nombre del producto : Prime H610M-K

ASUS Prime H610M-K. Fabricante de procesador: Intel, Socket de procesador: LGA 1700, Procesador compatible: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... tipos de memoria compatibles: DDR5-SDRAM, Memoria interna máxima: 96 GB, Tipo de ranuras de memoria: DIMM. Interfaces de disco de almacenamiento soportados: M.2, SATA III, Tipos de unidades de almacenamiento admitidas: HDD & SSD. Tipo de conector USB: USB tipo A. Tipo de interfaz ethernet: Gigabit Ethernet



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	PS/2 ports quantity	1
Processor socket *	LGA 1700	VGA (D-Sub) ports quantity *	1
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® Gold	HDMI ports quantity *	1
		Headphone outputs	1
Memory	DDR5-SDRAM 2 DIMM Dual-channel Non-ECC 4800,5000,5200,5400,5600 MHz 96 GB ✓	Line-in	✓
		Microphone in	✓
		USB connector type	USB Type-A
		Network	
		Ethernet LAN	✓
		Ethernet interface type	Gigabit Ethernet
		Wi-Fi *	✗
Storage controllers	HDD & SSD M.2, SATA III 4 5	Features	
		Motherboard chipset *	Intel H610
		Audio output channels *	7.1 channels
		Product colour	Multicolour
		Component for *	PC
Internal I/O	1 1 4 ✓ ✓ ✓	Motherboard form factor *	micro ATX
		Motherboard chipset family *	Intel
		Windows operating systems supported	Windows 10 x64, Windows 11
		Expansion slots	
		PCI Express x1 (Gen 3.x) slots	1
BIOS	128 Mbit	PCI Express x16 (Gen 4.x) slots	1
		Number of M.2 (M) slots	1
		BIOS	
ATX Power connector (24-pin)	✓	BIOS type *	UEFI AMI
		BIOS memory size	128 Mbit

Internal I/O		BIOS	
CPU fan connector	✓	Clear CMOS jumper	✓
Number of chassis fan connectors	2	Packaging data	
EPS power connector (8-pin)	✓	Package width	270 mm
Number of COM connectors	1	Package depth	263 mm
TPM connector	✓	Package height	51.5 mm
12V power connector	✓	Package weight	820 g
RGB LED pin header	✓	Weight & dimensions	
Rear panel I/O ports		Width	234 mm
USB 2.0 ports quantity *	4	Depth	203 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Height	36.5 mm
Ethernet LAN (RJ-45) ports *	1	Packaging content	
		Cables included	SATA
		Other features	
		Weight	470 g



4711387336328

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date