



## Commercial, Industrial and Residential Electrical Products

# 4 In. Square Box, Drawn, 1-1/2 In. Deep with One 1/2 In. and Eleven 3/4 In. KO's, Raised Ground

Catalog #: 191



#### **FEATURE BENEFIT**

Shallow box for installation in walls or ceilings for light fixtures, switches or receptacles

#### **PRODUCT FEATURES**

- Ideal for exposed work applications
- Combination screw heads allow quick installation
- Drawn construction
- Eleven 3/4 In. knockouts and One 1/2 In. knockout
- 21.0 Cu. In. capacity
- Raised ground, 10 In. #12 stranded copper pigtail
- Acceptable in 2-hour fire rated walls

#### **APPLICATIONS**

- Designed to enclose electrical wiring, switches, receptacles or lighting fixtures
- Constructed from 1/16 In. pre-galvanized steel
- 8-32 cover mounting screws assembled

### **CERTIFICATIONS**



#### PRODUCT SPECIFICATIONS

UPC Number: 050169901915 Ea Length/Depth (in.): 1.563

Ea Length/Depth (in.): 1.563
Ea Width (in.): 4.00
Ea Height (in.): 4.00
Wt. Ea. (Lbs.): 0.665
Package Type: Loose
Product UPC-A Labeled: No



Case I2of5: 50050169901910

Standard Carton Qty: 50 Min Order Qty: 50





All RACO single-gang, two-gang, 4 In. square, and single gang gangable U.L. listed steel boxes are acceptable for use in 2-hour fire rated walls. For additional information, consult U.L. "Fire Resistance Directory" or the U.L. website at www.ul.com



Per UL 514-A, suitable for use without a bonding jumper in circuits up to 600 volts

Revision 1, December 2019



RACO 3902 W. Sample St. South Bend, IN 46619 574-234-7151 www.hubbell.com/raco/en

