



Dahua Technology WizMind IPC-HDW5449TMP-SE-LED-0280B

Torreta Cámara de seguridad IP Interior y exterior 2688 x 1520

Píxeles Techo/pared

Marca : Dahua Technology

Familia de productos:
WizMind

Código del producto: DH-IPC-
HDW5449TMP-SE-LED-0280B

Nombre del producto : IPC-
HDW5449TMP-SE-LED-0280B

Dahua Technology WizMind IPC-HDW5449TMP-SE-LED-0280B. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Negro, Factor de forma: Torreta. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 107°, Ángulo de visión del objetivo, vertical: 60°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 1.8 mm (1 / 1.8"), Número de píxeles efectivos (A x V): 2688 x 1520 Píxeles. Distancia de detección: 58.2 m, Distancia de observación: 23.3 m, Distancia de reconocimiento: 11.6 m

Performance		Video	
Type *	IP security camera	Noise reduction technology	3D noise reduction
Placement supported *	Indoor & outdoor	Privacy masking	✓
Connectivity technology *	Wired	Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Wide Dynamic Range (WDR)	✓	Bit rate	H.264: 3 kbps-20480 kbps H.265: 3 kbps-20480 kbps
Day/night mode	✓	Back Light Compensation (BLC)	✓
Dynamic range	140 dB	Highlight Compensation (HLC)	✓
Certification	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B UL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07	Region of Interest (ROI) encoding	✓
Design		Audio	
Form factor *	Turret	Audio formats supported	G.711 A-law, G.711 µ-law, G.723, G.726, PCM
Mounting type *	Ceiling/wall	Signal-to-Noise Ratio (SNR)	56 dB
Product colour *	Black	Built-in microphone	✓
Housing material	Metal	Network	
Camera		Ethernet LAN *	✓
Angle of rotation	360°	Ethernet interface type	Fast Ethernet
Lens viewing angle, horizontal	107°		IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; 802.1x; SNMP
Lens viewing angle, vertical	60°	Supported network protocols	
Lens viewing angle, diagonal	135°	Number of users	20 user(s)
Tilt angle range	0 - 78°	Quality of Service (QoS) support	✓
Pan range	0 - 360°	Storage	
White balance	Auto, Manual, Natural, Outdoor, Street lamp	Card reader integrated	✓
Camera shutter speed	1/3 -1/100000 s	Compatible memory cards	MicroSD (TransFlash)
Adjustment shutter speed	Auto/Manual	Maximum memory card size	256 GB
Image sensor		Internal memory	512 MB
Number of sensors	1	ROM capacity	128 MB
Optical sensor size	25.4 / 1.8 mm (1 / 1.8")	Ports & interfaces	
Progressive scan	✓	Ethernet LAN (RJ-45) ports	1
Sensor type *	CMOS	Security	
Number of effective pixels (H x V)	2688 x 1520 pixels	Intelligent Video Surveillance (IVS) system features	Abandoned object, Face detection, Heat map, Intrusion, Missing object, People counting, Tripwire
Lens system		Mirror	✓
Number of lenses *	1	Management features	
Detect distance	58.2 m	Web browser	✓
Observe distance	23.3 m		
Recognize distance	11.6 m		
Focal length range	2.8 mm		

Lens system	
Maximum aperture number	1
Identify distance	5.8 m
Night vision	
Night vision *	✓
Night vision distance	30 m
LED type	IR
Number of illumination LEDs	2
Video	
Maximum resolution *	2688 x 1520 pixels
Total megapixels *	4 MP
Video formats supported	H.264+, H.265+
Video compression formats	H.264, H.264B, H.264H, H.265
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440, 2688 x 1520
Supported video modes	720p, 1080p
Frame rate	60 fps
Noise reduction	✓

Power	
Power source type *	DC, PoE
Power consumption (typical)	2.4 W
Power consumption (max)	6.5 W
Power consumption (Power over Ethernet (PoE))	3 W
DC output voltage	12
Operational conditions	
Operating temperature (T-T)	-40 - 60 °C
Storage temperature (T-T)	-40 - 60 °C
Operating relative humidity (H-H)	0 - 95%
System requirements	
Mobile operating systems supported	Android, iOS
Weight & dimensions	
Height	104.4 mm
Diameter	12.2 cm
Weight	500 g
Packaging data	
Package weight	680 g
Packaging content	
Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date