



Dahua Technology PoE DH-S4101-16ET2GF-240-C dispositivo de redes Gestionado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Familia de productos: PoE

Código del producto: DH-S4101-16ET2GF-240-C



Nombre del producto : DH-S4101-16ET2GF-240-C

Dahua Technology PoE DH-S4101-16ET2GF-240-C. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 7.2 Gbit/s. Estándares de red: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. Energía sobre Ethernet (PoE)



Management features		Power	
Switch type *	Managed	AC input voltage	100 - 240 V
Switch layer	L2	AC input frequency	50/60 Hz
Cloud-managed	✓	Input current	2 A
Ports & interfaces		Power consumption (typical)	240 W
Basic switching RJ-45 Ethernet ports quantity *	16	Power consumption (max)	240 W
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	Power over Ethernet (PoE)	
Fast Ethernet (copper) ports quantity	16	Power over Ethernet (PoE) *	✓
Gigabit Ethernet (copper) ports quantity	2	Power over Ethernet (PoE) ports quantity	16
Combo SFP ports quantity	2	Power over Ethernet (PoE) power per port	90 W
Network		Operational conditions	
Networking standards *	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt	Operating temperature (T-T)	-10 - 55 °C
10G support *	✗	Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating relative humidity (H-H)	5 - 95%
Data transmission		Storage relative humidity (H-H)	5 - 95%
Switching capacity *	7.2 Gbit/s	Weight & dimensions	
Forwarding rate	5.36 Mpps	Width	440 mm
MAC address table *	16000 entries	Depth	300 mm
Packet buffer memory	4 MB	Height	44 mm
Design		Weight	3.2 kg
Product colour	Black	Packaging data	
Performance		Package width	528 mm
Mean time between failures (MTBF)	371069 h	Package depth	412 mm
		Package height	112 mm
		Package weight	4.3 kg

Power		Certificates	
Power source *	AC	Certification	CE; FCC
Power supply included *	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date