

StarTech.com 10G2A1C25EPD-USB-HUB base para laptop o replicador de puertos Alámbrico USB 3.2 Gen 2 (3.1 Gen 2) Type-C Gris

Marca : StarTech.com

Código del producto: 10G2A1C25EPD-USB-HUB

Nombre del producto : 10G2A1C25EPD-USB-HUB

StarTech.com 10G2A1C25EPD-USB-HUB. Tecnología de conectividad: Alámbrico, Interfaz de host: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, Envío de energía de USB hasta: 100 W. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000,2500 Mbit/s, Estándares de red: IEEE 802.3bz. Color del producto: Gris, Velocidad de transferencia de datos: 10 Gbit/s, Indicadores LED: Actividad, Enlace. Tipo de alimentación: USB, Longitud del cable USB: 0.305 m. Certificados de sustentabilidad: CE, RoHS



Puertos e Interfaces		Condiciones ambientales	
Tecnología de conectividad *	Alámbrico	Intervalo de temperatura operativa (T-T)	0 - 40 °C
Interfaz de host *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C	Intervalo de temperatura de almacenaje	-10 - 70 °C
Cantidad de puertos tipo C USB 3.2 Gen 1 (3.1 Gen 1)	1	Intervalo de humedad relativa para funcionamiento	10 - 85%
Cantidad de puertos tipo A USB 3.2 Gen 2 (3.1 Gen 2)	2	Sustentabilidad	
Cantidad de puertos tipo C USB 3.2 Gen 2 (3.1 Gen 2)	1	Cumplimiento de la sostenibilidad	✓
Suministro de potencia USB	✓	Certificados de sustentabilidad	CE, RoHS
Revisión de envío de energía de USB	3.0	Peso y dimensiones	
Envío de energía de USB hasta	100 W	Ancho	163 mm
Entrada de micrófono *	✗	Profundidad	34 mm
Red		Altura	15 mm
Ethernet *	✓	Peso	68 g
Puertos Ethernet LAN (RJ-45)	1	Empaquetado de datos	
Ethernet LAN, velocidad de transferencia de datos	10,100,1000,2500 Mbit/s	Ancho del paquete	170 mm
Conexión lista LAN	✓	Largo del paquete	142 mm
Estándares de red	IEEE 802.3bz	Alto del paquete	30 mm
Desempeño		Peso del paquete	129 g
Lector de tarjeta integrado *	✗	Contenido del empaque	
Velocidad de transferencia de datos	10 Gbit/s	Guía de configuración rápida	✓
Color del producto *	Gris	Datos de logística	
Indicadores LED	Actividad, Enlace	Cantidad por caja principal	60 pieza(s)
Material de la cubierta	Plástico	Largo de la caja principal	500 mm
Control de energía		Longitud de la caja principal	320 mm
Tipo de alimentación	USB	Alto de la caja principal	210 mm
Longitud del cable USB	0.305 m		

#### Otras características

Circuito integrado	VIA - VL103, VIA - VL822, Realtek - RTL8156B
--------------------	--



0065030900676



065030900676

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-JAN-2024. Prints or copies of Information are only valid on the printed Publication date