

StarTech.com 10G2A1C25EPD-USB-HUB base para laptop o replicador de puertos Alámbrico USB 3.2 Gen 2 (3.1 Gen 2) Type-C Gris

Marca : StarTech.com

Código del producto:
10G2A1C25EPD-USB-HUB

Nombre del producto : Hub USB-C de 3 Puertos con Red Ethernet de 2,5Gbps y Entrega de Alimentación PD de 100W de Paso - USB 3.2 10Gbps - Ladrón de 2 Puertos USB-A - 1 Puerto USB Tipo C

StarTech.com Hub USB-C de 3 Puertos - Red Ethernet de 2,5Gbps - PD 100W - USB 3.2 10Gbps - Ladrón 2x USB-A - 1x USB Tipo C
StarTech.com 10G2A1C25EPD-USB-HUB. Tecnología de conectividad: Alámbrico, Interfaz de host: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, Envío de energía de USB hasta: 100 W. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000,2500 Mbit/s, Estándares de red: IEEE 802.3bz. Color del producto: Gris, Velocidad de transferencia de datos: 10 Gbit/s, Indicadores LED: Actividad, Enlace. Tipo de alimentación: USB, Longitud del cable USB: 0.305 m. Ancho: 163 mm, Profundidad: 34 mm, Altura: 15 mm



Ports & interfaces		Operational conditions	
Connectivity technology *	Wired	Operating temperature (T-T)	0 - 40 °C
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C	Storage temperature (T-T)	-10 - 70 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Operating relative humidity (H-H)	10 - 85%
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Sustainability	
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Sustainability compliance	✓
USB Power Delivery (USB PD)	✓	Weight & dimensions	
USB Power Delivery revision	3.0	Width	163 mm
USB Power Delivery up to	100 W	Depth	34 mm
Microphone in *	✗	Height	15 mm
Network		Weight	68 g
Ethernet LAN *	✓	Packaging data	
Ethernet LAN (RJ-45) ports	1	Package width	170 mm
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Package depth	142 mm
Wake-on-LAN ready	✓	Package height	30 mm
Networking standards	IEEE 802.3bz	Package weight	129 g
Performance		Packaging content	
Card reader integrated *	✗	Quick start guide	✓
Data transfer rate	10 Gbit/s	Technical details	
Product colour *	Grey	Compliance certificates	CE, RoHS
LED indicators	Activity, Link	Logistics data	
Housing material	Plastic	Products per master (outer) case	60 pc(s)
Power		Master (outer) case width	500 mm
Power source type	USB	Master (outer) case length	320 mm
USB cable length	0.305 m	Master (outer) case height	210 mm

Other features

Chipset

VIA - VL103, VIA - VL822, Realtek -
RTL8156B



0065030900676



065030900676

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date