

## Brother MFCL3780CDW Impresora multifunción LED A4 2400 x 600 DPI 31 ppm Wifi

**Marca :** Brother

**Código del producto:** MFCL3780CDW

**Nombre del producto :** MFCL3780CDW

- Impresión rápida de calidad láser de hasta 31 páginas por minuto y velocidades de escaneado de hasta 29/22 ipm (negro/color)  
 - Amplia bandeja de papel con capacidad para 250 hojas  
 - Conectividad inalámbrica integrada de dos bandas, Wi-Fi Direct®, Gigabit Ethernet e interfaz USB A4, 2400 x 600 dpi, Color LED, 31/31ppm, Ethernet, USB 2.0, WLAN, 3.5" Color Touchscreen, 21.7 kg Brother MFCL3780CDW. Tecnología de impresión: LED, Impresión: Impresión a color, Resolución máxima: 2400 x 600 DPI, Velocidad de impresión (color, calidad normal, A4/US Carta): 31 ppm. Copiando: Copia a color, Resolución máxima de copia: 600 x 600 DPI. Escaneando: Escaneo a color, Resolución óptica de escáner: 1200 x 1200 DPI. Enviando por fax: Fax a color. Funciones de doble cara: Copiar, Fax, Imprimir, Escanear. Tamaño máximo de papel ISO A-series: A4. Wifi. Color del producto: Blanco



Printing		Paper handling	
Print technology *	LED	Paper tray media types *	Envelopes, Glossy paper, Labels, Letterhead, Recycled paper
Printing *	Colour printing	ISO A-series sizes (A0...A9) *	A4, A5, A6
Duplex printing *	✓	ISO B-series sizes (B0...B9)	B5, B6
Maximum resolution *	2400 x 600 DPI	Non-ISO print media sizes	Executive, Folio, Legal, Letter
Print speed (black, normal quality, A4/US Letter) *	31 ppm	Paper tray media weight	60 - 163 g/m²
Print speed (colour, normal quality, A4/US Letter)	31 ppm	Ports & interfaces	
Secure printing	✓	USB port	✓
Copying		USB 2.0 ports quantity	1
Duplex copying *	✓	Network	
Copying *	Colour copying	Wi-Fi *	✓
Maximum copy resolution *	600 x 600 DPI	Ethernet LAN *	✓
Copier resize	25 - 400%	Cabling technology	10/100/1000Base-T(X)
N-in-1 copy function	✓	Wi-Fi Direct	✓
N-in-1 copy function (N=)	2, 4	Near Field Communication (NFC)	✓
Scanning		Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP
Duplex scanning *	✓	Supported network protocols (IPv4)	APIPA (Auto IP), ARP, BOOTP, CIFS Client, Custom Raw Port/Port 9100, DHCP, DNS Resolver, FTP Client and Server, HTTP/HTTPS Server, ICMP, IMAP4, IPP/IPPS, LDAP, LLNMR
Scanning *	Colour scanning		Responder, LPR/LPD, mDNS, POP3, RARP, SMTP Client, SNMPv1/v2c/v3, SNTP Client, TELNET Server, TFTP Client and Server, Web Services (Print/Scan), WINS/NetBIOS Name Resolution
Optical scanning resolution *	1200 x 1200 DPI		
Optical scanning resolution (ADF)	600 x 600 DPI		
Scanner type *	Flatbed & ADF scanner		
Scan to	Cloud, E-mail, E-mail Server, FTP, Network folder, USB		
Scan drivers	SANE, TWAIN, WIA		
Fax			
Duplex faxing	✓		

Fax		Network	
Faxing *	Colour faxing	Supported network protocols (IPv6)	NDP, RA, DNS Resolver, mDNS, LLMNR Responder, LPR/LPD, Custom Raw Port/Port 9100, IPP/PPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, TELNET Server, SNMPv1/v2c/v3, HTTP/HTTPS Server, TFTP Client and Server, ICMPv6, SNMP Client, LDAP, Web Services (Print/Scan), IMAP4
Modem speed	33.6 Kbit/s		
Fax memory	500 pages		
Features		Mobile printing technologies	Apple AirPrint, Mopria Print Service
Duplex functions *	Copy, Fax, Print, Scan	Performance	
Number of print cartridges *	4	Internal memory *	512 MB
Printing colours *	Black, Cyan, Magenta, Yellow	Built-in processor	✓
Page description languages	BR-Script 3, PCL 5c, PCL 5e, PCL 6, PDF 1.7, XPS	Processor frequency	800 MHz
Input & output capacity		Design	
Total number of input trays *	1	Product colour *	White
Total input capacity *	250 sheets	Market positioning *	Home & office
Total output capacity *	150 sheets	Built-in display *	✓
Multi-Purpose tray	✓	Display diagonal	8.89 cm (3.5")
Multi-Purpose tray input capacity	30 sheets	Control type	Touch
Auto document feeder (ADF)	✓	Colour display	✓
Auto document feeder (ADF) input capacity	50 sheets	System requirements	
Paper handling		Windows operating systems supported	✓
Maximum ISO A-series paper size *	A4	Mac operating systems supported	✓
		Linux operating systems supported	✓
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Operating temperature (T-T)	10 - 32 °C
		Weight & dimensions	
		Width	410 mm
		Depth	462 mm
		Height	401 mm
		Weight	21.7 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date