



Dahua Technology DH-CS4006-4GT-60 dispositivo de redes Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: DH-CS4006-4GT-60

Nombre del producto : DH-CS4006-4GT-60

Dahua Technology DH-CS4006-4GT-60. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 6. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 12 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Voltaje de entrada DC: 53 V. Energía sobre Ethernet (PoE). Montaje de pared

Management features		Security	
Switch type *	Managed	DHCP features	DHCP client
Switch layer	L2	Design	
Quality of Service (QoS) support	✓	Product colour	Black
Web-based management	✓	Housing material	Metal
Cloud-managed	✓	Reset button	✓
Ports & interfaces		LED indicators	✓
Basic switching RJ-45 Ethernet ports quantity *	6	Wall mountable	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity	6	Power source *	DC
Network		DC input voltage	53 V
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x	Input current	1.226 A
10G support *	✗	Power consumption (max)	65 W
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Power over Ethernet (PoE)	
Full duplex	✓	Power over Ethernet (PoE) *	✓
Flow control support	✓	Power over Ethernet (PoE) ports quantity	4
Link aggregation	✓	Operational conditions	
Spanning tree protocol	✓	Operating temperature (T-T)	-10 - 55 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	5 - 95%
Virtual LAN features	Port-based VLAN	Storage relative humidity (H-H)	5 - 95%
Number of VLANs	32	Weight & dimensions	
Data transmission		Width	130 mm
Switching capacity *	12 Gbit/s	Depth	90 mm
Forwarding rate	8.93 Mpps	Height	26 mm
MAC address table *	8000 entries	Weight	290 g
Jumbo frames support	✓	Packaging data	
Jumbo frames	15000	Package width	265 mm
		Package depth	238 mm
		Package height	76 mm
		Package weight	940 g



6923172571144

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date