

## Dahua Technology PFS3016-16GT-M No administrado L2 Gigabit Ethernet (10/100/1000) 1U Negro

Marca: Dahua Technology Código del producto: DH-PFS3016-16GT-M

Nombre del producto: PFS3016-16GT-M

Dahua Technology PFS3016-16GT-M. Tipo de interruptor: No administrado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 16. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 32 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Voltaje de entrada DC: 12 V. Montaje de pared, Montaje en rack, Factor de forma: 1U

Management features		Design	
Switch type *	Unmanaged	LED indicators	✓
Switch layer	L2	Wall mountable	✓
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	16	Fanless	✓
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Power	
type *	· · · · · · · · · · · · · · · · · · ·	Power source *	AC
Network		Power supply included *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	DC input voltage	12 V
	002.3u, ILLE 002.3x	Power over Ethernet (PoE)	
Data transmission		Power over Ethernet (PoE) *	×
Switching capacity *	32 Gbit/s	One wational conditions	
Forwarding rate	23.68 Mpps	Operational conditions	
MAC address table *	8000 entries	Operating temperature (T-T)	-10 - 55 °C
Jumbo frames support	✓	Storage temperature (T-T)	-40 - 85 °C
Jumbo frames	10000	Operating relative humidity (H-H)	5 - 95%
Packet buffer memory	2 MB	Storage relative humidity (H-H)	5 - 95%
Design		Weight & dimensions	
Rack mounting *	<b>✓</b>	Width	235 mm
Form factor	1U	Depth	103 mm
Product colour	Black	Height	27 mm
Housing material	Metal		

