

## Dahua Technology WizSense DH-IPC-HDW2249T-S-IL cámara de vigilancia Domo Cámara de seguridad IP 1920 x 1080 Pixeles Techo/pared/Tubo

Marca: Dahua Technology

Familia de productos: WizSense Código del producto: DH-IPC-

HDW2249T-S-IL

Nombre del producto: DH-

IPC-HDW2249T-S-IL

Dahua Technology WizSense DH-IPC-HDW2249T-S-IL. Tipo: Cámara de seguridad IP, Tecnología de conectividad: Alámbrico, Rango dinámico: 120 Db. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Domo. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 107°, Ángulo de visión del objetivo, vertical: 56°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de visión nocturna: 30 m, Tipo de LED: IR/Blanco

Performance		Video	
Type *	IP security camera	Privacy masking	<b>✓</b>
Connectivity technology *	Wired	Bit rate control	Constant Bit Rate (CBR)/Variable Bit
Wide Dynamic Range (WDR)	<b>✓</b>	Back Light Compensation (BLC)	Rate (VBR)  ✓
Day/night mode	<b>✓</b>		<b>V</b>
Infrared (IR) cut-off filter	✓	Highlight Compensation (HLC)	
Built-in light	✓	Region of Interest (ROI) encoding	<b>✓</b>
Dynamic range	120 dB	Audio	
Certification	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B	Audio formats supported	G.711 A-law, G.711 μ-law, G.726, PCM
		Signal-to-Noise Ratio (SNR)	56 dB
			30 dB
Design		Network	
Form factor *	Dome	Ethernet LAN *	<b>✓</b>
Mounting type *	Ceiling/Wall/Pole	Ethernet interface type	Fast Ethernet
Product colour *	White	Consideration of controls	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP;
Housing material  Protection features	Metal, Plastic  Dust resistant	Supported network protocols	SFTP; DHCP; DNS; DDNS; NTP;
International Protection (IP) code	IP67	Number of users	Multicast; ICMP; IGMP
	11 07		6 user(s)  ✓
Camera		Quality of Service (QoS) support Streaming method	Multicast
Minimum illumination	0 lx		Multicast
Angle of rotation  Lens viewing angle, horizontal	360° 107°	Storage	
Lens viewing angle, vertical	56°	Internal memory	128 MB
Lens viewing angle, diagonal	127°	ROM capacity	128 MB
Tilt angle range	0 - 78°	Ports & interfaces	
Pan range	0 - 360°	Ethernet LAN (RJ-45) ports	1
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Security	
Camera shutter type	Electronic	Video motion detection	✓
Camera shutter speed	1/3 -1/100000	Active tampering alarm	✓
Image sensor		Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Number of sensors	1	Management features	
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Web browser	<b>✓</b>
Progressive scan	✓ cuos	Management software	DSS;DMSS
Sensor type *	CMOS	Power	
Lens system		Power source type *	DC, PoC
Minimum aperture number	1.6	Power consumption (typical)	1.6 W
Night vision		DC output voltage	12
Night vision *	✓		

Night vision		Operational conditions	
Night vision distance LED type Number of illumination LEDs	30 m IR/White 2	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 60 °C -40 - 60 °C 0 - 95%
Video		System requirements	
Maximum resolution *	1920 x 1080 pixels	Mobile operating systems supported Android, iOS	
Total megapixels *	2 MP	Weight & dimensions	
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265	Width	100.9 mm
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)	Diameter Weight	11 cm 370 g
		Packaging data	
Video streaming	✓	Package weight	510 g
Gain control type	Auto/Manual	Packaging content	
Flip & mirror	✓	Number of cameras *	1

