



Dahua Technology WizSense DH-IPC-HDW1439V-A-IL cámara de vigilancia Domo Cámara de seguridad IP 2560 x 1440 Píxeles Techo/pared/Tubo

Marca : Dahua Technology

Familia de productos:
WizSense

Código del producto: DH-IPC-HDW1439V-A-IL

Nombre del producto : DH-IPC-HDW1439V-A-IL

- Sensor de imagen CMOS de 4 MP 1/2,9", baja luminosidad e imagen de alta definición
 - Salidas máx. 4 MP (2560 × 1440) a 25/30 fps
 - Códec H.265, alta tasa de compresión, tasa de bits ultrabaja
 - LED IR integrado y luz cálida, máx. La distancia de iluminación IR es de 30 m y la distancia de luz cálida es de 30 m
 - WDR, 3D NR, HLC, BLC, marca de agua digital, aplicable a diversas escenas de monitoreo
 - ROI, SMART H.264 +/-H.265+, codificación flexible, aplicable a diversos entornos de ancho de banda y almacenamiento
 - Detección de anomalías: Detección de movimiento, manipulación de vídeo, detección de audio, desconexión de red, conflicto de IP y acceso ilegal
 - Micrófono incorporado
 - Fuente de alimentación de 12 VDC/PoE, fácil de instalar
 - Protección IP67
 - Soporta la detección humana
- CMOS 1/2,9", 2560 x 1440, 128 megas, Progresivo, Automático/Manual 1/3 s-1/100.000, Hasta 30 m, Focal fija, 2,8mm; 3,6mm, F1.6, IP67, RJ-45 (10/100 Base-T)

Performance		Video	
Type *	IP security camera	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Connectivity technology *	Wired	Back Light Compensation (BLC)	✓
Wide Dynamic Range (WDR)	✓	Highlight Compensation (HLC)	✓
Day/night mode	✓	Region of Interest (ROI) encoding	✓
Infrared (IR) cut-off filter	✓	Audio	
Certification	CE-LVD: EN 62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	Audio formats supported	G.711 A-law, G.711 µ-law, G.726, PCM
Design		Signal-to-Noise Ratio (SNR)	56 dB
Form factor *	Dome	Network	
Mounting type *	Ceiling/Wall/Pole	Ethernet LAN *	✓
Product colour *	White	Ethernet interface type	Fast Ethernet
Housing material	Metal, Plastic	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multidifusión; ICMP; IGMP; P2P
Protection features	Dust resistant	Quality of Service (QoS) support	✓
International Protection (IP) code	IP67	Streaming method	Multicast
Camera		Storage	
Minimum illumination	0.0006 lx	Internal memory	128 MB
Angle of rotation	360°	ROM capacity	128 MB
Lens viewing angle, horizontal	94°	Ports & interfaces	
Lens viewing angle, vertical	52°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, diagonal	111°	Security	
Tilt angle range	0 - 78°	Video motion detection	✓
Pan range	0 - 360°	Active tampering alarm	✓
White balance	Auto, Manual, Natural, Outdoor, Regional custom	Management features	
Camera shutter type	Electronic	Web browser	✓
Camera shutter speed	1/3 -1/100000	Management software	PSS inteligente Lite; DSS; DMSS
Image sensor			
Number of sensors	1		
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")		
Progressive scan	✓		

Image sensor		Power	
Sensor type *	CMOS	Power source type *	DC, PoE
Night vision		Power consumption (typical)	2 W
Night vision *	✓	DC output voltage	12
Night vision distance	30 m	Operational conditions	
LED type	IR	Operating temperature (T-T)	-40 - 60 °C
Video		Storage temperature (T-T)	-40 - 60 °C
Maximum resolution *	2560 x 1440 pixels	Operating relative humidity (H-H)	0 - 95%
Total megapixels *	4 MP	System requirements	
Video formats supported	H.264, H.265	Mobile operating systems supported Android, iOS	
Video compression formats	H.264, H.264+, H.264B, H.264H, H.265, H.265+	Weight & dimensions	
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2304 x 1296, 2560 x 1440	Width	100.9 mm
		Diameter	11 cm
		Weight	330 g
		Packaging data	
Video streaming	✓	Package weight	450 g
Gain control type	Auto/Manual	Packaging content	
Flip & mirror	✓	Number of cameras *	1
Privacy masking	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date