

Dahua Technology HDCVI PTZ SD49218DBN-HC Domo Cámara de seguridad CCTV Interior y exterior 1920 x 1080 Pixeles Techo/pared

Marca : Dahua Technology Familia de productos: HDCVI Código del producto: DH-PTZ SD49218DBN-HC

Nombre del producto:

SD49218DBN-HC

Dahua Technology HDCVI PTZ SD49218DBN-HC. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Negro, Blanco, Factor de forma: Domo. Iluminación mínima: 0.0005 Lux, Ángulo de visión del objetivo, horizontal: 60.6 - 3.8°, Ángulo de visión del objetivo, vertical: 34.1 - 2.1°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8°). Zoom óptico: 18x, Zoom digital: 16x, Distancia de detección: 1241.4 m





Performance		Lens system	
Type *	CCTV security camera	Minimum aperture number	1.6
Placement supported *	Indoor & outdoor	Closest focusing distance	0.1 m
Connectivity technology *	Wired	Night vision	
PTZ control	✓	Night vision *	/
PTZ modes	5 Pattern, 5 Scan, 8 Tour, Preset point	Night vision distance	100 m
PTZ protocols	DH-SD, Pelco-P/D	LED type	IR
Tour recording	✓	Number of illumination LEDs	6
Preset points	✓	Video	
Wide Dynamic Range (WDR)	✓	Maximum resolution *	1920 x 1080 pixels
Day/night mode	✓	Total megapixels *	2 MP
Alarm input/output	✓	Supported graphics resolutions	704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Design		Supported video modes	720p, 1080p
Form factor *	Dome	Frame rate	60 fps
Mounting type *	Ceiling/wall	Noise reduction	✓
Product colour * International Protection (IP) code	Black, White IP66	Noise reduction technology	2D noise reduction, 3D noise reduction
Fog proof	√	Gain control type	Auto/Manual
	•	Back Light Compensation (BLC)	✓
Camera		Highlight Compensation (HLC)	✓
Camera pan control	✓	Audio	
Camera tilt control	✓		1 channels
Minimum illumination	0.0005 lx	Audio input channels	1 Channels

Camera		Audio	
Lens viewing angle, horizontal	60.6 - 3.8°	Signal-to-Noise Ratio (SNR)	50 dB
Lens viewing angle, vertical	34.1 - 2.1°	Network	
3 3 , 3	69.4 - 4.4°	Ethernet LAN *	×
Tilt proset speed	-15 - 90° 200 °/sec	Wi-Fi *	×
Tilt preset speed Tilt manual speed	0.1 - 120 °/sec 0 - 360° 240 °/sec 0.1 - 200 °/sec ✓ Auto, Indoor, Manual, Natural, Outdoor, Sodium lamp, Street lamp	Bluetooth *	×
Pan range		Storage	
Pan preset speed		Built-in HDD *	×
Pan manual speed		ROM capacity	128 MB
Auto flip		RAM capacity	256 MB
White balance		Ports & interfaces	
Camera shutter type	Electronic	RS-485 ports	1
Camera shutter speed	1/3 - 1/30000 s	BNC output ports	1
Image sensor		Security	
Number of sensors	1	Alarm input channels	2
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Alarm output channels	1
Progressive scan	√	Power	
Sensor type *	CMOS	Power source type *	DC
Lens system		Power consumption (typical)	10 W
Zoom capability	1	Power consumption (max)	22 W
Optical zoom	18x	DC output voltage DC output current	12 3 A
Digital zoom Number of lenses *	16x 1	·	J.A.
Detect distance	1241.4 m	Operational conditions	40. 70.00
Observe distance	490.3 m	Operating temperature (T-T)	-40 - 70 °C
Recognize distance	248.3 m	Weight & dimensions	
Focal length range	5 - 90 mm	Height	269.9 mm
Auto focus	1	Diameter Weight	16 cm 3 kg
Focus	Manual 2.9	3	3 kg
Maximum aperture number Identify distance	2.9 124.1 m	Packaging data	401
racinity distance	124.1 111	Package weight	4.2 kg
		Sustainability	
		Compliance certificates	CE, Federal Communications Commission (FCC), UL
		Packaging content	
		Number of cameras *	1

