



## Dahua Technology DHI-NVR4232-16P-4KS3 grabadora de vídeo en red (NVR) 1U Negro

**Marca :** Dahua Technology

**Código del producto:** DHI-NVR4232-16P-4KS3

**Nombre del producto :** DHI-NVR4232-16P-4KS3

Dahua Technology DHI-NVR4232-16P-4KS3 NVR 4k / 32 Canales IP /16 Puertos PoE / Rendimiento 160 Mbps/2 Bahías disco duro/ 4 2 E S Alarma/WizSense/ 2 canales SMD Plus -



Desempeño		Puertos e Interfaces	
Canales de entrada de vídeo *	32 canales	Puertos de salida VGA (D-Sub)	1
Canales de entrada de alarma	4	Cantidad de puertos USB 2.0	2
Canales de salida de alarma	2	Interfase RS-232	✓
Máxima resolución *	3840 x 2160 Pixeles	Puerto - RS-232	1
Resoluciones soportadas	3840 x 2160, 1920 x 1080, 1280 x 1024, 1280 x 720	Protocolos de red compatibles	HTTP; HTTPS; TCP/IP; IPv4; IPv6; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search
Detección de movimiento en video	✓	<b>Características</b>	
Formatos de vídeo compatibles	H.264, H.264+, H.265, H.265+	Montaje en rack	✓
Sistema operativo instalado	LINUX incrustado	Capacidad del rack	1U
Imagen instantánea	✓	Color del producto	Negro
Ancho de banda de entrada	160 Mbit/s	<b>Control de energía</b>	
Detector de rostro	✓	Voltaje de entrada AC	100 - 240 V
<b>Características de LAN inalámbrico</b>		Frecuencia de entrada AC	50/60 Hz
Wifi *	✗	<b>Condiciones ambientales</b>	
<b>Disco duro</b>		Intervalo de temperatura operativa (T-T)	-10 - 55 °C
Número de HDDs soportados	2	Intervalo de humedad relativa para funcionamiento	10 - 93%
Capacidad máxima de almacenaje *	20 TB	Intervalo de temperatura de almacenaje	-20 - 60 °C
Interfaz del HDD *	SATA	<b>Peso y dimensiones</b>	
<b>Puertos e Interfaces</b>		Ancho	375 mm
Puertos Ethernet LAN (RJ-45) *	1	Profundidad	327.9 mm
Energía sobre Ethernet (PoE)	✓	Altura	53 mm
Ethernet LAN, velocidad de transferencia de datos	10,100,1000 Mbit/s	Peso	2.6 kg
Cantidad de puertos Power over Ethernet (PoE)	16	Ancho del paquete	451 mm
Número de puertos HDMI	1	Largo del paquete	147 mm
		Alto del paquete	425 mm
		Peso del paquete	3.8 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-OCT-2024. Prints or copies of Information are only valid on the printed Publication date