Dahua Technology DH-CS4226-24ET-240 dispositivo de redes Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: DH-CS4226-24ET-240

Nombre del producto : DH-CS4226-24ET-240

Dahua Technology DH-CS4226-24ET-240. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 26. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 8.8 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Energía sobre Ethernet (PoE). Montaje en rack

Management features

Switch type *	Managed
Switch layer	L2
Web-based management	✔

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	26
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	24
SFP module slots quantity	2

Network

Networking standards *	IEEE 802.3, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z
10G support *	✘
VLAN support	✔
Number of VLANs	32

Data transmission

Switching capacity *	8.8 Gbit/s
Forwarding rate	6.55 Mpps
MAC address table *	8000 entries
Jumbo frames support	✔
Jumbo frames	15000
Packet buffer memory	4 MB

Security

DHCP features	DHCP client

Design

Rack mounting *	✔
Product colour	Black
Housing material	Metal
Reset button	✔

Performance

Mean time between failures (MTBF)	562.765 h

Power

Power source *	AC
Power supply included *	✔
Power consumption (max)	265 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✔
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	240 W

Operational conditions

Operating temperature (T-T)	-10 - 55 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	5 - 95%
Storage relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	220 mm
Depth	440 mm
Height	44 mm
Weight	2.47 kg

Packaging data

Package width	342 mm
Package depth	540 mm
Package height	90 mm
Package weight	3.12 kg

6923172571267