

Dahua Technology DHI-ASI7213S-W lector de control de acceso Terminal de reconocimiento facial Negro, Plata

Marca: Dahua Technology Código del producto: DHI-ASI7213S-W

Nombre del producto : DHI-ASI7213S-W

Dahua Technology DHI-ASI7213S-W. Tipo de visualizador: LCD, Diagonal de la pantalla: 17.8 cm (7"), Máxima resolución: 1024 x 600 Pixeles. Tipo de cámara frontal: Cámara única, Tipo de sensor: CMOS, Total de megapixeles: 2 MP. Protocolos de red compatibles: UDP; TCP; IPv4; RTSP; SIP; P2P; RTP. Voltaje de entrada: 12 V, Corriente de entrada: 2 A, Consumo energético: 24 W. Ancho: 118 mm, Profundidad:

24.2 mm, Altura: 218 mm

Technical details		Display	
Type * Authentication type * LED indicators	Face recognition terminal Access chip/card, Face recognition, Password Status	Maximum resolution Screen shape Touchscreen Touchscreen technology	1024 x 600 pixels Flat ✓ Capacitive
Wiegand interface	✓		Sapasiano
Fingerprint reader *	×	Camera	
Access chip/card reader *	✓	Front camera *	✓ Cinale comere
Alarm function	✓	Front camera type Sensor type	Single camera CMOS
Cards capacity	100000 cards	Total megapixels	2 MP
Face capacity	50000	Wide Dynamic Range (WDR)	✓ · · · · · · · · · · · · · · · · · · ·
Face recognition distance	0.3 - 2 m		•
Face recognition duration	0.2 s	Performance	
Face recognition accuracy	99.9%	Built-in processor	✓
User capacity	50000 user(s)	Ports & interfaces	
Temperature alarm	✓	Wi-Fi	✓
Password capacity	50000		1
Record capacity	300000	Ethernet LAN (RJ-45) ports Supported network protocols	
Interoperability	CGI;ONVIF	RS-232 ports	UDP; TCP; IPv4; RTSP; SIP; P2P; RTP
Open Supervised Device Protocol (OSDP)	✓	RS-485 ports	1
Software development kit (SDK) support	✓	USB port	✓
Voice prompts	✓	Alarm input/output	•
Exit button	✓	Power	
Lock control	✓	Input voltage	12 V
Web-based management	✓	Input current	2 A
Unlock function	/	Power consumption (typical)	24 W
Real-time surveillance	/	Weight & dimensions	
Remote verification	✓	Width	118 mm
Duress alarm	1	Depth	24.2 mm
Active tampering alarm	·	Height	218 mm
Holiday period	128 h	Packaging data	
QR code	√	Package width	299 mm
Product colour	Black, Silver	Package depth	164 mm
Housing material	Polycarbonate (PC), Tempered glass	Package height	72 mm
	rolycalboliate (FC), Tellipered glass	Package weight	670 g
Display		Packaging content	
Built-in display *	•	Power adapter included	✓
Display type	LCD	Operational conditions	
Display diagonal	17.8 cm (7")	Operational conditions	20 55 96
		Operating temperature (T-T) Operating relative humidity (H-H)	-20 - 55 °C 0 - 90%

