



Dahua Technology DHI-ASI7213K-W lector de control de acceso Terminal de reconocimiento facial

Marca : Dahua Technology

Código del producto: DHI-ASI7213K-W

Nombre del producto : DHI-ASI7213K-W



Dahua Technology DHI-ASI7213K-W. Tipo de visualizador: LCD, Diagonal de la pantalla: 17.8 cm (7"), Tamaño de la pantalla (HxV): 600 x 1024 mm. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Total de megapíxeles: 2 MP. Consumo energético: 12 W, Rango de voltaje DC: 12 V, Corriente directa (max): 2 A. Ancho: 213 mm, Profundidad: 116 mm, Altura: 28.6 mm

Detalles técnicos		Exhibición	
Tipo *	Terminal de reconocimiento facial	Tipo de visualizador	LCD
Tipo de autenticación *	chip/tarjeta de acceso, Reconocimiento facial, Contraseña	Diagonal de la pantalla	17.8 cm (7")
Interfaz de Wiegand	✓	Tamaño de la pantalla (HxV)	600 x 1024 mm
Lector de chip/tarjeta de acceso *	✓	Pantalla táctil	✓
Tipo de lector de chip/tarjeta de acceso	Sin contacto	Cámara fotográfica	
Capacidad de tarjetas	100000 tarjetas	Cámara frontal *	✓
Distancia de lectura del lector RFID (identificación por radiofrecuencia)	4 mm	Tipo de sensor	CMOS
Canales de entrada de alarma	1	Tamaño del sensor óptico	25.4 / 2.8 mm (1 / 2.8")
Canales de salida de alarma	1	Total de megapíxeles	2 MP
Capacidad facial	50000	Amplio rango dinámico (WDR)	✓
Distancia de reconocimiento facial	0.3 - 3 m	Luz infrarroja (IR)	✓
Duración del reconocimiento de huellas dactilares	0.2 s	Puertos e Interfaces	
Precisión del reconocimiento facial	99.9%	Wifi	✓
Capacidad de los usuarios	100000 usuario(s)	Puertos RS-485	1
Capacidad de la contraseña	50000	Puerto USB	✓
Capacidad de registro	300000	Alarma de entrada / salida	✓
Indicaciones de voz	✓	Control de energía	
Botón de salida	✓	Consumo energético	12 W
Alarma de coacción	✓	Rango de voltaje DC	12 V
Operado remotamente	✓	Corriente directa (max)	2 A
Alarma de manipulación activa	✓	Peso y dimensiones	
Período de vacaciones	128 h	Ancho	213 mm
Código QR	✓	Profundidad	116 mm
Código IP (International Protection)	IP65	Altura	28.6 mm
Exhibición		Peso	1.2 kg
Pantalla incorporada *	✓	Contenido del empaque	
		Soporte(s) de montaje incluido	✓
		Adaptador de corriente incluido	✓
		Condiciones ambientales	
		Intervalo de temperatura operativa (T-T)	-30 - 60 °C
		Intervalo de humedad relativa para funcionamiento	0 - 90%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-APR-2024. Prints or copies of Information are only valid on the printed Publication date