

Dahua Technology DHI-ASI7213K-W lector de control de acceso Terminal de reconocimiento facial

Marca : Dahua Technology Código del producto: DHI-ASI7213K-W

Nombre del producto : DHI-ASI7213K-W

Dahua Technology DHI-ASI7213K-W. Tipo de visualizador: LCD, Diagonal de la pantalla: 17.8 cm (7"), Tamaño de la pantalla (HxV): 600 x 1024 mm. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"), Total de megapixeles: 2 MP. Consumo energético: 12 W, Rango de voltaje DC: 12 V, Corriente directa (max): 2 A. Ancho: 213 mm, Profundidad: 116 mm, Altura: 28.6 mm

Technical details		Display	
Type *	Face recognition terminal	Display size (HxV)	600 x 1024 mm
Authentication type *	Access chip/card, Face recognition, Password	Touchscreen	✓
Wiegand interface	✓	Camera	
Access chip/card reader * Access chip/card reader type Contactless Cards capacity 100000 cards AFID reading distance 4 mm Alarm input channels 1	Front camera * Sensor type Optical sensor size Total megapixels Wide Dynamic Range (WDR)	CMOS 25.4 / 2.8 mm (1 / 2.8") 2 MP	
Alarm output channels	1 50000	Infrared (IR) light	✓
Face recognition distance		Ports & interfaces	
acce recognition distance ingerprint recognition duration acce recognition accuracy 399.9% Iser capacity 300000 Iserord capacity 50000 Iserord capacity Indicate the service of the servic	Wi-Fi RS-485 ports USB port Alarm input/output Power Power Power consumption (typical) DC voltage range DC current (max) Weight & dimensions Width Depth Height Weight	1	
Display		Packaging content	
Built-in display * Display type Display diagonal	LCD 17.8 cm (7")	Mounting bracket(s) included Power adapter included Operational conditions Operating temperature (T-T) Operating relative humidity (H-H)	-30 - 60 °C 0 - 90%

