



Dahua Technology DH-CS4226-24ET-375 Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: DH-CS4006-4ET-60

Nombre del producto : DH-CS4226-24ET-375

Dahua Technology DH-CS4226-24ET-375. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 6. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 4.8 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x. Energía sobre Ethernet (PoE). Montaje de pared

Management features		Performance	
Switch type *	Managed	Mean time between failures (MTBF) 2039105 h	
Switch layer	L2		
Web-based management	✓		
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	6	Power source *	AC
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power supply included *	✓
Fast Ethernet (copper) ports quantity	4	Power consumption (max)	65 W
Gigabit Ethernet (copper) ports quantity	2	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) ports quantity	4
10G support *	✗	Power over Ethernet (PoE) power per port	30 W
VLAN support	✓	Total Power over Ethernet (PoE) budget	60 W
Number of VLANs	32	Other features	
Data transmission		Ethernet interface type	Fast Ethernet, Gigabit Ethernet
Switching capacity *	4.8 Gbit/s	Operational conditions	
Forwarding rate	3.57 Mpps	Operating temperature (T-T)	-10 - 55 °C
MAC address table *	8000 entries	Storage temperature (T-T)	-40 - 70 °C
Jumbo frames support	✓	Operating relative humidity (H-H)	5 - 95%
Jumbo frames	9216	Storage relative humidity (H-H)	5 - 95%
Packet buffer memory	4 MB	Weight & dimensions	
Security		Width	130 mm
DHCP features	DHCP client	Depth	90 mm
Design		Height	26 mm
Rack mounting *	✗	Weight	280 g
Product colour	Black	Packaging data	
Housing material	Metal	Package width	238 mm
LED indicators	Uplink	Package depth	265 mm
Wall mountable	✓	Package height	76 mm
		Package weight	920 g



6923172571175

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date