

## Sharp PN-ME552 pantalla de señalización Pantalla plana de señalización digital 139.7 cm (55") LCD 450 cd / m² 4K Ultra HD Negro Android

**Marca :** Sharp

**Código del producto:** PN-ME552

**Nombre del producto :** PN-ME552

Sharp PN-ME552. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 139.7 cm (55"), Tecnología de visualización: LCD, Resolución de la pantalla: 3840 x 2160 Píxeles, Brillo de pantalla: 450 cd / m², Tipo HD: 4K Ultra HD. Sistema operativo instalado: Android. Color del producto: Negro

Display		Design	
Panel type	ADS	Placement supported *	Indoor
LED backlight	✓	Product colour *	Black
LED backlighting type	Direct-lit LED	VESA mounting *	✓
Display diagonal *	139.7 cm (55")	Panel mounting interface	400 x 400 mm
Display technology *	LCD	<b>Performance</b>	
Display resolution *	3840 x 2160 pixels	Purpose *	Commercial
Display brightness *	450 cd/m²	HDCP	✓
HD type *	4K Ultra HD	<b>Power</b>	
Touchscreen *	✗	Power consumption (typical) *	120 W
Response time	8 ms	Power consumption (standby) *	0.5 W
Contrast ratio (typical)	1200:1	Power consumption (max)	220 W
Viewing angle, horizontal	178°	Energy efficiency class (SDR)	G
Viewing angle, vertical	178°	<b>Computer system</b>	
Display number of colours	1.07 billion colours	Computer system *	✓
Pixel pitch	0.32 x 0.32 mm	Operating system installed	Android
Horizontal scan range	15 - 135 kHz	Operating system version	13
Vertical scan range	23 - 76 Hz	<b>Weight &amp; dimensions</b>	
High Dynamic Range (HDR) supported	✓	Display width	1233 mm
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10), Hybrid Log-Gamma (HLG)	Display depth	62 mm
Native refresh rate	60 Hz	Display height	703.5 mm
<b>Ports &amp; interfaces</b>		Display weight	13.2 kg
HDMI ports quantity *	3	<b>Packaging data</b>	
HDMI version	2.0	Package width	1332 mm
DVI port *	✗	Package depth	156 mm
USB port *	✓	Package height	819 mm
USB connector type	USB Type-A, USB Type-C	Package weight	29.5 kg
Ethernet LAN *	✓	<b>Operational conditions</b>	
Wi-Fi *	✗	Operating relative humidity (H-H)	20 - 80%
RS-232C	✓	Storage temperature (T-T)	-20 - 60 °C
<b>Audio</b>		Storage relative humidity (H-H)	10 - 80%
Built-in speaker(s) *	✓	<b>Technical details</b>	
<b>Design</b>		Sustainability compliance	✓
Product design *	Digital signage flat panel	Sustainability certificates	ENERGY STAR



0805736078619



805736078619

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date