



Dahua Technology DH-XVR1B04H-I videograbadora digital Negro



Marca : Dahua Technology

Código del producto: DH-XVR1B04H-I

Nombre del producto : DH-XVR1B04H-I

Dahua Technology DH-XVR1B04H-I. Color del producto: Negro, Máxima resolución de video: 1920 x 1080 Pixeles, Formatos de compresión de video: H.264, H.264+, H.265, H.265+. Tipo de interfaz ethernet: Ethernet rápido, Protocolos de red compatibles: HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm..., Número de usuarios: 128 usuario(s). Interfaz del HDD: SATA, Capacidad máxima del HDD: 6 TB. Tipo de fuente de alimentación: CC, Voltaje CD: 12 V. Ancho: 198 mm, Profundidad: 202.9 mm, Altura: 41.5 mm

Performance		Network	
Maximum video resolution	1920 x 1080 pixels	Ethernet LAN	✓
Video compression formats	H.264, H.264+, H.265, H.265+	Ethernet interface type	Fast Ethernet
Audio formats supported	AAC, G.711, PCM	Ethernet LAN (RJ-45) ports	1
Backup function	✓	Supported network protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P,IP Search
Video motion detection	✓		
Playback resolutions supported	1920×1080, 1280×1024, 1280×720		
Channels quantity	4 channels	Number of users	128 user(s)
Product colour *	Black	Hard drive	
Playback modes	Fast, Next, Pause, Play, Previous, Repeat, Shuffle, Slow, Stop, Zoom	Number of HDDs supported	1
Analog signal format system	NTSC, PAL	HDD interface	SATA
Operating system installed	Embedded LINUX	Maximum HDD capacity	6 TB
PTZ control	✓	Power	
Rack capacity	1U	Power supply type	DC
	CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN 50130; EN 55024	DC voltage	12 V
Certification		Weight & dimensions	
Ports & interfaces		Width	198 mm
		Depth	202.9 mm
		Height	41.5 mm
		Weight	550 g
BNC input ports	4	Packaging content	
BNC output ports	1	Cables included	AC
HDMI ports quantity	1	AC adapter included	✓
VGA (D-Sub) output ports	1	Quick start guide	✓
Audio input	1	Operational conditions	
Audio output	1	Operating temperature (T-T)	-10 - 45 °C
USB 2.0 ports quantity	2	Storage temperature (T-T)	-20 - 70 °C

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date