
Verbatim CDS-17 Alámbrico USB 3.2 Gen 1 (3.1 Gen 1) Type-C Negro, Gris

Marca : Verbatim Código del producto: 32172

Nombre del producto: CDS-17







Ports & interfaces			
roits & litterlaces		Performance	
Connectivity technology *	Wired	Country of origin	China
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Power	
USB 2.0 ports quantity *	1	Power source type	DC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Power supply	120 W
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Output voltage Output current	20 V 6 A
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1	Software	
USB Power Delivery (USB PD)	✓	Windows operating systems supported	Windows 10, Windows 11
USB Power Delivery up to	100 W	Mac operating systems supported	Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac
HDMI ports quantity *	3		
DisplayPorts quantity	2		
DisplayPort version	1.4		
Combo headphone/mic port	✓		
Headphone outputs *	1		
Headphone connectivity	3.5 mm		OS X 13.0 Ventura
DC-in jack	✓	Operational conditions	
Network		Operating temperature (T-T)	0 - 40 °C
Ethernet LAN *	✓	Storage temperature (T-T)	-20 - 85 °C
Ethernet LAN (RJ-45) ports	1	Operating relative humidity (H-H)	20 - 90%
Ethernet LAN data rates	1000 Mbit/s	Storage relative humidity (H-H)	5 - 95%
Performance		Sustainability	
Card reader integrated *	✓	Sustainability compliance	✓
Compatible memory cards	MicroSD (TransFlash), SD	Weight & dimensions	
Data transfer rate	10 Gbit/s	Width	100 mm
	8K Ultra HD		
HD type Cable lock slot	ok oiti a fib	Depth	180 mm

Performance		Weight & dimensions	
Cable lock slot type	Kensington Black, Grey Status ✔	Weight	998 g
Product colour * LED indicators		Packaging data	
Plug and Play		Quantity per pack Package width	1 pc(s) 175 mm
Housing material Acrylonitrile butadiene styrene (ABS), Aluminium	,	Package depth Package height	243 mm 66 mm
	Package weight	1.22 kg	
		Technical details	
		Compliance certificates	REACH, RoHS





023942321729

0023942321729

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.