



DELL PowerEdge R360 servidor 2 TB Bastidor (1U) Intel Xeon E E-2478 2.8 GHz 16 GB DDR5-SDRAM 600 W

Marca : DELL

Familia de productos:
PowerEdge

Código del producto:
R360FY25Q1MX



Nombre del producto : R360

- No OS
- Intel Xeon E-2478 (24MB Cache, 2.8GHz)
- 16GB (4800MHz) DDR5-SDRAM & 4000GB HDD
Intel Xeon E-2478 (24MB Cache, 2.8GHz), 16GB DDR5-SDRAM (4800MHz), 4000GB HDD, LAN, PERC H755, 2 x 600W, No OS
DELL PowerEdge R360. Familia de procesador: Intel Xeon E, Frecuencia del procesador: 2.8 GHz, Modelo del procesador: E-2478. Memoria interna: 16 GB, Tipo de memoria interna: DDR5-SDRAM. Capacidad total de almacenaje: 2 TB, Tamaño del HDD: 3.5". Ethernet. Fuente de alimentación: 600 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Bastidor (1U)



Processor		Network	
Processor manufacturer *	Intel	Ethernet interface type	Gigabit Ethernet
Processor family *	Intel Xeon E	Ports & interfaces	
Processor model *	E-2478	Ethernet LAN (RJ-45) ports *	2
Processor frequency *	2.8 GHz	USB 2.0 ports quantity	2
Processor boost frequency	5.2 GHz	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1
Performance cores	8	VGA (D-Sub) ports quantity	1
Processor cores	8	Serial ports quantity	1
Processor cache	24 MB	Expansion slots	
Number of processors installed	1	PCI Express x8 slots	1
Thermal Design Power (TDP)	80 W	PCI Express x16 slots	1
Processor threads	16	Design	
Memory		Chassis type *	Rack (1U)
Internal memory *	16 GB	Product colour	Black
Internal memory type *	DDR5-SDRAM	Software	
Buffered memory type	Unregistered (unbuffered)	Operating system installed *	✗
Memory slots	4x DIMM	Compatible operating systems *	Canonical® Ubuntu® Server LTS
ECC	✓		Microsoft® Windows Server® with Hyper-V RedHat® Enterprise Linux
Memory clock speed	4800 MHz		SUSE® Linux Enterprise Server
Memory data transfer rate	4800 MT/s		VMware® ESXi®
Maximum internal memory *	128 GB	Power	
Storage		Redundant power supply (RPS) support *	✓
Total storage capacity *	2 TB	Power supply *	600 W
Number of HDDs installed	2	Number of redundant power supplies supported	2
HDD capacity	2 TB		
HDD size	3.5"		
Number of HDDs supported	4		
Supported HDD sizes	3.5"		
RAID support *	✗		

Storage		Power	
Supported RAID controllers	PERC H755	Number of redundant power supplies installed	2
Optical drive type *	✗	Power cable connector 1	NEMA 5-15P
Network		Power cable connector 2	C13 coupler
Ethernet LAN	✓	Weight & dimensions	
		Width	482 mm
		Height	42.8 mm

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date