



Dahua Technology Lite DH-HAC-HDW1200TQ-A cámara de vigilancia Domo Cámara de seguridad CCTV Interior y exterior 1920 x 1080 Pixeles Techo/pared/Tubo

Marca : Dahua Technology

Familia de productos: Lite

Código del producto: DH-HAC-HDW1200TQ-A

Nombre del producto : DH-HAC-HDW1200TQ-A

Dahua Technology Lite DH-HAC-HDW1200TQ-A. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Negro, Blanco, Factor de forma: Domo. Iluminación mínima: 0.001 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 83°. Tipo de sensor: CMOS. Distancia de detección: 50.9 m, Distancia de observación: 20.3 m, Distancia de reconocimiento: 10.2 m

Performance		Night vision	
Type *	CCTV security camera	Night vision distance	40 m
Placement supported *	Indoor & outdoor	LED type	IR
Connectivity technology *	Wired	Number of illumination LEDs	1
Wide Dynamic Range (WDR)	✓	Video	
Day/night mode	✓	Maximum resolution *	1920 x 1080 pixels
Certification	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; FCC: 47 CFR FCC Part 15, Subpart B	Total megapixels *	2 MP
		Frame rate	30 fps
		Noise reduction	✓
Design		Noise reduction technology	3D noise reduction
Form factor *	Dome	Gain control type	Auto
Mounting type *	Ceiling/Wall/Pole	Privacy masking	✓
Product colour *	Black, White	Back Light Compensation (BLC)	✓
Housing material	Metal, Plastic	Highlight Compensation (HLC)	✓
International Protection (IP) code	IP67	Digital Wide Dynamic Range (DWDR)	✓
Camera		Smart IR	✓
Minimum illumination	0.001 lx	Audio	
Angle of rotation	360°	Signal-to-Noise Ratio (SNR)	65 dB
Lens viewing angle, horizontal	83°	Ports & interfaces	
Lens viewing angle, vertical	48°	BNC output ports	1
Lens viewing angle, diagonal	105°	Security	
Tilt angle range	0 - 78°	Mirror	✓
Pan range	0 - 360°	Power	
White balance	Area white balance, Auto	Power source type *	DC
Camera shutter type	Electronic	Power consumption (max)	3.2 W
Camera shutter speed	1/25 - 1/100000 s	DC output voltage	12
Number of Privacy masking areas	8	Operational conditions	
Image sensor		Operating temperature (T-T)	-40 - 60 °C
Progressive scan	✓	Storage temperature (T-T)	-40 - 60 °C
Sensor type *	CMOS	Operating relative humidity (H-H)	0 - 95%
Lens system		Storage relative humidity (H-H)	0 - 95%
Detect distance	50.9 m	Weight & dimensions	
Observe distance	20.3 m	Height	100.9 mm
Recognize distance	10.2 m	Diameter	11 cm
Maximum aperture number	2	Weight	320 g
Identify distance	5.1 m	Packaging data	
Fixed focal length	3.6 mm	Package weight	490 g
Closest focusing distance	0.5 m		
Night vision			
Night vision *	✓		

Packaging content

Number of cameras * 1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date