

GIGABYTE GP-P650G unidad de fuente de alimentación 650 W
20+4 pin ATX ATX Negro

Marca : GIGABYTE

Código del producto: GP-P650G

Nombre del producto : GP-P650G

GIGABYTE GP-P650G. Potencia total: 650 W, Voltaje de entrada AC: 100 - 240 V, Corriente de entrada: 12 - 6 A. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 50 cm, Longitud del cable de alimentación SATA: 150,500 mm. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Bronze. Color del producto: Negro, Tipo de enfriamiento: Activo, Diámetro de ventilador: 12 cm. Ancho: 140 mm, Profundidad: 150 mm, Altura: 86 mm



Power		Ports & interfaces	
Total power *	650 W	PCI Express power cable length	65 cm
AC input voltage *	100 - 240 V	CPU P4 connector (4-pin)	1
Input current	12 - 6 A	CPU power connector (4+4 pin)	✓
Maximum input current (@110V)	12 A	CPU power cable length	60 cm
Maximum input current (@220V)	6 A	ATX power connector (20+4 pin)	✓
Power Factor Correction (PFC) type	Active	Floppy disk drive connector	✓
Combined power (+3.3V)	120 W	Cabling type	Non-Modular
Combined power (+12V)	650 W	Performance	
Combined power (+5V)	650 W	80 PLUS certification *	80 PLUS Bronze
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	12.5 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	2.31
Max output current (+12V)	54.17 A	Noise level	39 dB
Max output current (+5V)	20 A	Bearing technology	HDB
Max output current (-12V)	0.3 A	Mean time between failures (MTBF)	100000 h
Max output current (+5Vsb)	20 A	Design	
Power protection features	Over power, Overcharge, Short circuit, Under voltage	Product colour	Black
Ports & interfaces		Cooling type	Active
Motherboard power connector *	20+4 pin ATX	Fan diameter	12 cm
Motherboard power cable length	50 cm	Number of fans	1 fan(s)
Number of SATA power connectors	6	Fan location	Top
SATA power cable length	150,500 mm	On/off switch	✓
Peripheral (Molex) power connectors (4-pin) *	3	Weight & dimensions	
Peripheral (Molex) power cable length	150,500 mm	Width	140 mm
PCI Express power connectors (6+2 pin)	4	Depth	150 mm
		Height	86 mm

Packaging data

Package type

Box



4719331553753

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date