

## Dahua Technology Lite DH-HAC-HFW1509T(-A)-LED cámara de vigilancia Bala (forma) Cámara de seguridad CCTV Interior y exterior Techo/pared

Marca : Dahua Technology Familia de productos: Lite Código del producto: DH-HAC-HFW1509T(-A)-LED

Nombre del producto : DH-HAC-HFW1509T(-A)-LED

Dahua Technology Lite DH-HAC-HFW1509T(-A)-LED. Tipo: Cámara de seguridad CCTV, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de inclinación: 0 - 180°, Rango de paneo: 0 - 360°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"), Número de píxeles efectivos (A x V): 2592 x 1944 Pixeles. Distancia focal fija: 3.6 mm, Distancia más cercana de enfoque: 2.1 m

Performance		Video	
Type * Placement supported * Connectivity technology * Wide Dynamic Range (WDR)  Certification	CCTV security camera Indoor & outdoor Wired  ✓ CE (EN55032, EN55024, EN50130-4,EN60950-1)FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)UL (UL60950-1+CAN/CSA C22.2 No.60950-1)	Total megapixels * Noise reduction Noise reduction technology Privacy masking Back Light Compensation (BLC) Highlight Compensation (HLC) Digital Wide Dynamic Range (DWDR)	5 MP  ✓  Ultra 2D noise reduction  ✓  ✓
Design		Audio	
Form factor * Mounting type *	Bullet Ceiling/wall	Signal-to-Noise Ratio (SNR) Built-in microphone	65 dB ✓
Product colour *	White	Network	
Housing material International Protection (IP) code	Metal IP67	Ethernet LAN * Wi-Fi *	× ×
Camera		Bluetooth *	x
Camera pan control Camera tilt control	<b>/</b>	Storage Built-in HDD *	×
Minimum illumination  Angle of rotation	0 lx 360°	Security	
Tilt angle range	0 - 180°	Mirror	✓
Pan range White balance Camera shutter type Camera shutter speed	0 - 360° Auto, Manual Electronic 1/30-1/100000	Power Power source type * Power consumption (typical) DC output voltage	DC 3 W 12
Image sensor		Operational conditions	12
Number of sensors Optical sensor size Progressive scan	1 25.4 / 2.7 mm (1 / 2.7")	Operating temperature (T-T) Storage temperature (T-T)	-40 - 60 °C -40 - 60 °C
Sensor type *	CMOS	Weight & dimensions	
Number of effective pixels (H x V)	2592 x 1944 pixels	Width Depth	174.5 mm 70.6 mm
Lens system  Number of lenses *	1	Height	72.3 mm
Fixed focus	· ✓	Weight	330 g
Maximum aperture number	1.2	Packaging data	
Fixed focal length	3.6 mm	Package weight	440 g
Closest focusing distance	2.1 m	Packaging content	
		Number of cameras *	1

