

ASUS ROG STRIX 1000W Gold Aura Edition unidad de fuente de alimentación 20+4 pin ATX ATX Negro

Marca : ASUS
Familia de productos: ROG
Código del producto: ROG-STRIX-1000G-AURA-GAMING

Nombre del producto : ROG STRIX 1000W Gold Aura Edition

ASUS ROG STRIX 1000W Gold Aura Edition. Potencia total: 1000 W, Voltaje de entrada AC: 100 - 240 V, Corrección del factor de potencia tipo (PFC): Activo. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 60 cm, Longitud del cable de alimentación SATA: 400,120 mm. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Gold. Color del producto: Negro, Tipo de enfriamiento: Activo, Número de ventiladores: 1 Ventilador(es). Cables incluidos: CPU, PCIe, SATA, Peripheral (Molex)



Power		Ports & interfaces	
Total power *	1000 W	PCI Express power connectors (16-pin)	1
AC input voltage *	100 - 240 V	PCI Express power cable length	70 cm
Power Factor Correction (PFC) type	Active	CPU power connector (4+4 pin)	✓
Combined power (+3.3V)	120 W	CPU power cable length	65 cm
Combined power (+12V)	996.6 W	Cabling type	Fully-Modular
Combined power (+5V)	120 W	Performance	
Combined power (-12V)	3.6 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5Vsb)	15 W	Purpose *	PC
Max output current (+3.3V)	22 A	Power supply unit (PSU) form factor *	ATX
Max output current (+12V)	83.3 A	ATX version	3.0
Max output current (+5V)	22 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	3 A	Cooling type	Active
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage	Number of fans	1 fan(s)
Ports & interfaces		Fan location	Top
Motherboard power connector *	20+4 pin ATX	Illumination	✓
Motherboard power cable length	60 cm	Packaging content	
Number of SATA power connectors	5	Cables included	CPU, PCIe, SATA, Peripheral (Molex)
SATA power cable length	400,120 mm	Certificates	
Peripheral (Molex) power connectors (4-pin) *	4	Compliance certificates	RoHS
Peripheral (Molex) power cable length	400,150 mm	Weight & dimensions	
PCI Express power connectors (8-pin)	4	Width	180 mm
		Depth	150 mm
		Height	86 mm
		Weight	3.03 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date